

## Index

### A, B

abc variables, 54, 94  
air-gap, 75, 82, 89, 114  
air-gap characteristic, 87, 96  
armature reaction, 107  
armature resistance, 87, 88  
armature winding, 50  
base quantities, 81, 82  
Behn-Eschenburg, 80, 98  
Blondel, 100, 107

### C

Canay, 76, 92, 95, 104, 113  
Canay inductance, 76, 113  
Cartesian flux observer, 282  
circuit, 50–54, 58, 59, 64, 65, 70–74,  
76, 78–80, 82, 83, 85, 86, 91, 92,  
94–96, 98, 100, 102, 103, 108, 109,  
111–113  
circuit change, 64, 66, 111  
Clarke, 64  
coenergy, 53, 54, 58, 66, 69, 100, 102  
constitutive equations, 58  
cross-saturation, 53, 83, 105, 107, 115

### D, E

damping circuit, 51, 83

direct current decay, 95  
discretization, 120, 128, 129, 131, 151,  
152, 155  
disturbance observer, 399  
electromagnetic torque, 50, 53, 58, 66  
electromotive force, 52, 54, 68, 69, 88,  
90, 98, 99  
estimation error, 42, 44, 46–53, 58, 64  
experiment design, 51, 54  
exponential, 92, 93, 95

### F, I

Faraday, 52, 54  
field system, 58, 88  
flux estimator, 178, 185, 187, 189,  
248  
flux observer, 286, 288, 290, 293, 301,  
302, 305–311, 314, 315, 317–319  
identifiability, 25  
identifiable, 42, 49, 55  
identification, 119–134, 138, 141, 144,  
146, 150, 153, 167–169, 171–173  
induction machine, 251, 252, 255, 258,  
260, 262, 264, 269, 271, 272,  
279–283, 286, 319  
induction motor, 119, 125–128, 132,  
138, 141, 143, 147, 150, 151, 153,  
158, 161, 168, 170–172, 174

inductive element, 52, 71, 77  
 internal angle, 78, 96, 100, 115  
 internal parameters, 85, 86, 92, 94  
 iron losses, 26, 29, 35, 37, 39, 47–55  
 isotropic, 111, 112

## J, K

Joule losses, 32, 78, 90  
 Kalman filter, 122, 123, 129, 131, 139,  
 141, 144–150, 152, 153, 155, 157–  
 161, 165–172, 174, 201–205, 211,  
 213, 218, 220, 222, 248

## L

leakage inductance, 75, 82, 92, 102,  
 103, 113, 115  
 least square method, 138  
 low slip test, 91  
 Luenberger observer, 122, 123, 129,  
 141, 157, 158, 160, 161, 163,  
 166–168, 172

## M, N

magnetic characteristic, 87–89, 96, 99,  
 101, 105, 107, 108, 110, 111, 114  
 magnetic losses, 52, 72, 76, 79, 80,  
 89, 90  
 magnetization inductance, 75, 88, 97,  
 101, 113  
 magnetizing current, 77, 88, 97, 99,  
 102, 114, 115  
 main flux, 75, 76, 77  
 measurement  
 error, 42, 44–46, 53, 57, 60, 64  
 noise, 46, 49, 52, 54, 59  
 mechanical losses, 90  
 model error, 42, 45, 48, 54, 60, 64  
 noise, 95  
 no-load test, 87, 90, 98

## O, P

operational reactance, 83, 84, 115  
 optimal experiment, 54  
 parameter sensitivity analysis, 285,  
 319  
 parameterization, 107  
 Park, 66, 70, 83, 101  
 per-unit, 80  
 pole pairs, 54  
 Potier, 49, 77, 79, 96, 98, 99, 104,  
 111–113  
 Potier inductance, 75, 82

## R

reduced order flux observers, 275  
 reduced order model, 128, 151, 152,  
 155, 157, 168  
 reduction of the number of elements,  
 74  
 redundant observer, 414, 452, 458  
 resistive element, 52  
 rotor base variables, 82

## S

salience factor, 111, 112  
 salient pole, 50, 97, 100, 114  
 saturation, 24, 25, 28, 29, 31, 37–39,  
 41, 42, 45, 47–50, 54  
 saturation factor, 97, 112, 113  
 sensorless control, 167, 248  
 sensorless PMSM, 458, 459  
 sinusoidal coupling hypothesis, 56,  
 60  
 smooth pole, 49, 50, 65, 77, 96, 99  
 static inductance, 98  
 subtransient, 84, 85, 94  
 symmetry group, 56, 60  
 synchronous reactance, 80, 85, 89,  
 91

**T**

Tellegen, 51  
Thevenin, 79  
three-phase link, 72  
three-phase short-circuit, 94,  
95  
three-phase symmetry, 58  
time constant, 84, 85, 92, 94, 95  
torque observation, 330, 367, 368, 375,  
381, 393, 399, 404  
transformation ratio, 75, 103

transient, 83–85, 91, 93–95, 114, 116  
two-phase symmetry, 65, 69

**U, V, Z**

unidentifiable, 19  
variable structure observer, 236, 238,  
241, 243–245  
vector control, 285, 301, 302, 319  
von der Embse, 100, 117  
zero-energy, 77, 79  
zero-power-factor, 99, 114