

# Index

## A

AC switch, 505, 506  
active clamping, 172, 175  
avalanche, 14, 15, 17, 51, 52, 55

## B

bipolar devices, 128  
bipolar diodes, 234  
breakdown  
  electric field, 189, 190, 192, 212  
  voltage, 190, 191, 192, 201, 219  
bus bars, 318, 319, 323, 327, 354, 362,  
  363, 397

## C

capacitive  
  coupling, 344, 349  
  effects, 31  
capacitors, 267, 268, 270, 271, 272, 276,  
  280, 281, 283, 284, 288, 289, 290,  
  291, 292, 293, 294, 295, 300, 301,  
  302, 303, 304, 310, 312, 313, 314,  
  315, 316  
  ceramic, 267, 312  
carrier lifetime, 98  
cell, 5, 10  
channel  
  inversion, 24, 26  
  resistance, 9, 10, 11, 21, 26, 46, 56  
common mode, 330, 351

commutation  
  cell, 403  
  modules, 137  
  speed, 144, 148, 152  
conducted disturbances, 351, 352, 353  
convection, 446, 447, 450, 452, 454, 456,  
  461, 463, 473, 475, 476, 488  
cooling, 433, 442, 445, 446, 447, 448,  
  449, 450, 451, 455, 463, 485, 487, 490,  
  494  
current  
  density, 2, 21, 23, 49, 54  
  critical density, 49  
  short circuit current, 92  
  theoretical density, 49

## D

derating, 142, 157, 174  
desaturated operation, 26  
design method and technologies, 535  
diamonds, 196  
dielectric, 267, 268, 269, 270, 272, 273,  
  274, 275, 276, 277, 278, 280, 281, 283,  
  285, 294, 295, 300, 301, 302, 303, 304,  
  305, 310, 315  
drain, 2, 5, 6, 7, 11, 14, 16, 19, 21, 24, 27,  
  28, 29, 32, 33, 35, 36, 38, 39, 40, 49,  
  52, 57, 58  
drift zone, 3, 8, 12, 16, 18, 23, 24, 27, 28,  
  32, 33, 46, 57  
dual thyristor, 507, 515, 516, 517  
dynamic operation, 31

**E**

electrodes, 301  
 electrodynamic efforts, 391, 394, 397,  
 398, 399  
 electron injection, 24, 26  
 EMC, 318, 351, 352, 353, 400  
 etching, 196, 204, 205, 209, 210, 213,  
 231, 232, 235, 245, 263

**F**

factor of merit, 202  
 ferroelectric materials, 295, 305  
 Flotherm, 476, 478  
 flow of  
   heat, 443, 444, 450, 452, 454, 455, 459,  
   463, 464, 465, 468, 477  
   fluid, 456, 458, 478, 496  
 Flux 3D, 473, 475, 476, 477  
 functional integration, 504, 507, 516, 520

**G**

gallium arsenide, 195  
 gallium nitride, 234, 254  
 gate, 3, 4, 5, 6, 8, 12, 13, 18, 19, 21, 24,  
 26, 27, 28, 31, 33, 35, 36, 37, 38, 39,  
 40, 41, 42, 48, 49, 56, 58  
   drive, 57, 73, 76, 79, 83, 88, 91, 114,  
   123, 126  
   oxide, 6, 13, 18, 26  
 grid  
   drive circuit, 157, 165  
   resistance, 408, 409, 411, 413, 414,  
   415, 417, 418, 425, 426, 427, 431

**I**

IEGT, 122  
 IGBT, 57, 58, 59, 60, 61, 62, 63, 64, 65,  
 69, 71, 72, 73, 74, 75, 76, 77, 79, 85-  
 137, 317, 319, 364, 365, 390, 391, 401,  
 410  
 impedance bridge, 365  
 IMS, 318, 319, 320, 321, 351, 353, 354,  
 360, 361  
 InCa3D, 320, 322, 329, 365, 366, 367,  
 368, 369, 370, 384, 400  
 inductance  
   partial inductance, 325, 354, 355, 356,  
   357, 361, 362

  switching mesh, of the, 408, 427  
   wiring inductance, 154, 157, 158  
 inductive coupling, 343  
 injection coefficient, 61, 68, 69, 70, 71,  
 83, 116  
 input capacitance, 12, 13, 34  
 integration, 449, 496, 497, 499, 500, 501,  
 502, 503, 504, 505, 507, 509, 510, 511,  
 512, 513, 514, 515, 517, 518, 519, 520,  
 521, 525, 527, 528, 529, 530, 531, 532,  
 535, 537, 538, 539, 541, 542, 543, 544,  
 545  
 interaction power-command, 407  
 interconnection, 318, 319, 321, 353, 354,  
 363, 368, 400  
 ion implantation, 204, 206, 210, 216, 235,  
 260

**J, L, M**

JFET, 10, 56  
 LAASTHERM, 472  
 losses, 22  
 majority carriers, 4  
 matrix connection, 138, 178  
 MESFET, 231, 232, 233, 256, 258, 263,  
 264  
 metallization, 196, 213, 214, 216  
 Miller voltage, 38, 40  
 mixed junction diodes, 234  
 mobilities, 193  
 modeling  
   and use of capacitors, 283  
   connections, 317  
   heat exchanges, 461  
 modulation, 59, 67, 68, 71  
 monocrystal growth, 197  
 monolithic integration, 499, 504  
 multiplication factor M, 61

**O**

OFF state, 26, 29  
 ON state, 26  
 optical commands, 165  
 output capacitance, 34  
 over-constrained operations, 48  
 oxidation, 209

**P, R**

parallel connection, 128, 138, 139, 140, 141, 144, 154, 156, 158, 159, 165, 177, 183, 184, 185

parasitic  
capacitances, 156, 160, 169, 170, 178, 410, 428, 429  
transistor, 59

passive clamping, 172

PEEC, 320, 323, 324, 325, 332, 338, 368, 371, 376, 377, 383, 384, 385, 391, 400

permittivity, 269, 270, 275, 294, 295, 296, 300, 303, 304, 305, 307, 314

printed wiring, 330, 350, 351, 353

protections, 123, 133

recombination rate, 65, 68, 83, 98

resistance  $RD_{son}$ , 23

**S**

safe operating areas, 54, 55

saturated zone, 36

saturation speed, 189, 194

security areas, 111

series connection, 90, 133, 138, 141, 143, 144, 146, 156, 165, 166, 167, 168, 169, 170, 171, 172, 177, 178, 179, 181, 183, 184, 185, 187

SiC (silicon carbide), 185-268  
MOSFET, 225, 255  
Schottky diode, 221-225, 228, 255

SiC-3C, 203

SiC-4H, 187, 188, 196, 211, 245

SiC-6H, 187, 188, 211, 214, 215, 216

silicon critical field, 14, 20

SIT (static induction transistor), 231, 232, 233

skin effect, 322, 324, 328, 330, 344, 349, 351, 357

snubbers, 267, 283, 294

source, 3, 5, 6, 7, 8, 10, 11, 13, 14, 18, 19, 21, 23, 24, 26, 27, 29, 31, 33, 37, 48

static operation, 26

stored charges, 63, 67, 68, 83, 91, 98, 115, 120, 123

sustaining voltage, 19, 20, 55, 57  
peripheral sustaining voltage, 20

switch  
-off, 39, 40, 41, 42, 44, 53, 57  
-on, 38, 39, 42, 43

switching  
hard switching, 73, 76, 77, 86, 87, 92, 94, 97, 101, 112  
losses, 422, 428  
soft switching, 88, 89, 90, 91

**T**

$\tan \delta d$ , 274, 275

temperature, 4, 13, 22, 23, 30, 46, 47, 48, 50, 51, 52, 54, 55  
coefficient, 98, 99, 100  
distribution, 442, 490

thermal  
conductivity, 189, 195, 198, 213, 251  
resistance, 445, 452, 454, 455, 456, 475, 487, 492  
spreading layer, 22

thermography, 487, 488, 489, 490

thermo-sensible parameter, 491

thermo-sensitive parameter, 492, 493

thin wire method, 331, 335, 336, 339, 342, 343, 344, 348

track, 333, 334, 335, 336, 337, 339, 341, 342, 343, 344, 347, 348, 349, 350, 360

transfer capacitance, 34

**U, V, Z**

unipolar devices, 4, 24

vertical structure, 2, 3, 7

ZCS (zero current switching), 90, 91, 93, 95, 96, 97, 101

ZVS (zero voltage switching), 88, 89, 90, 101, 136