

# Index

1-bit tag, 44

## A

accountability, 229-230, 233, 236-238, 248  
anti-collision algorithms, 147  
auto-ID, 3  
availability, 234, 240-241, 244, 248

## B, C

backscattering, 40, 48  
binary search, 49  
bistatic, 42  
channel hopping, 67, 70, 90-91  
collision, 48-49  
convergence, 191-195, 212, 220

## D-G

data protection, 192, 194, 218-219  
electromagnetic compatibility, 201  
end-to-end, 19, 21, 26, 30

EPCglobal, 3, 11-12, 193-194, 198-200, 203-207, 211, 226-227  
far-field, 40  
future  
Internet era, 3  
network, 13, 24, 31  
gateway, 20, 23, 30

## H

handover, 158, 165-169, 172-175, 188  
high frequency (HF), 36, 40, 42, 44  
home  
automation, 191, 213, 215  
networking, 126  
HomePlug, 98, 100-115  
host identity protocol (HIP), 202, 210

## I

ICANN, 227-229, 235, 250  
identification, 130, 134-136, 139, 141-151, 191-192, 196-199, 202-207, 212, 219

- IEEE, 193, 213-216
- IEEE 1901, 114
- IEEE 802.15.4, 108, 121, 126-127
- IETF, 193, 200, 202, 213-216, 221
- implications, 246-247
- indoor localization, 162, 170
- in-home, 98, 100-101, 112, 119, 126-127
- International Telecommunication Union – Telecommunication (ITU-T), 193, 195, 207-208, 211-212, 216
- Internet, 1-12, 19-26, 29-30
  - governance, 225, 246, 250
- Internet of Things (IoT), 1, 3, 7, 19, 21, 121, 126-129, 223-226, 229, 230-248
  - abstract view, 31
  - interoperability, 242-243, 247-248
- IP
  - addresses, 202, 206, 208, 209, 214
  - convergence, 30
- ISO/IEC, 193, 197-198, 200, 205-208
- ITU, 4, 5, 13, 23, 24
- L**
  - legislator, 232, 237
  - legitimacy, 224, 229-230, 233, 248-249
  - lifetime, 59, 64, 77, 86-87, 91
  - listen-before-talk, 49
  - load modulation, 38-39, 48
  - low frequency (LF), 36, 40
- M**
  - middleware, 45-48
- mobile IP, 158
- mobility management, 158-159, 164, 170, 176
- modulation, 40, 43-44, 64, 65
- monostatic, 43
- movement detection, 167-169, 172-175, 183, 186, 188
- multi-path fading, 66-67, 70, 75
- N, O**
  - next generation networks, 195, 216-217
  - object, 2, 4, 7-15, 19-23, 27, 29, 31
  - object identifier (OID), 207, 208
- P**
  - positioning algorithm, 161, 174-175, 188
  - power line communication (PLC), 97-127
  - privacy, 192, 217-219
- R**
  - radio spectrum, 201
  - read range, 36, 51
  - reader, 35-36, 39-52
  - reliability, 56-58, 67-68, 85, 89, 91, 241-242, 248
  - RFID, 157-159, 164, 169-178, 181-183, 187-188, 191-202, 207, 212-220
    - applications, 129, 139, 152
    - standards, 134
  - robustness, 239, 248
- S**
  - security, 55-59, 82, 88
  - smart dust, 54, 56

standardization, 71, 192-196, 201, 215-216, 220  
standards, 193-194, 197-199, 203  
synchronization, 76-77

## T

tag, 36, 39-45, 48-52  
threshold power, 50-51  
tracing, 130, 137, 139-144, 152  
tracking, 130-131, 139, 141-144, 152  
transparency, 224, 229-230, 233-235, 240, 248

## U, V

ubiquitous ID center, 193-194, 203, 206-207

ultra-high frequency (UHF), 36, 40, 42, 45  
uniform resource locator (URL), 211  
VeriSign, 227

## W

wireless networks, 159  
technologies, 160, 175  
wireless sensor networks (WSNs), 53, 55, 59, 67, 80-192, 213-214