



cPanel

tutorialspoint

SIMPLY EASY LEARNING

www.tutorialspoint.com

 <https://www.facebook.com/tutorialspointindia>

 <https://twitter.com/tutorialspoint>

About the Tutorial

cPanel is a Linux-based web hosting control panel. It provides graphical user interface and is packed with lots of features that automates the process of hosting a website. It is a premium software, which is developed by a private company, cPanel Inc.

cPanel has been written in Perl and was first released in March 21, 1996. It can only be installed in Linux servers, it supports CentOS, RHEL and CloudLinux operating software.

Nowadays most of the Linux webhosting servers use cPanel to host and manage websites on their servers. If a person purchases the hosting from companies like GoDaddy, Hostgator or even from smaller local companies, it is more likely that the hosting will come with cPanel.

In this tutorial, we will learn about managing and hosting a website with ease. This tutorial is divided as per the sections of cPanel and each section has the explanation of the functions it contains.

Audiences

This tutorial is prepared for anyone who has basic knowledge of computers as well as of websites. It will help all those readers who wish to host and manage a website using cPanel. After completing this tutorial, you will have a moderate level of expertise in using the automation tools available in cPanel.

Prerequisites

Before starting this tutorial, we assume that you have a domain and cPanel hosting already setup. If not, then we will also cover those topics briefly in the following chapters.

Copyright and Disclaimer

© Copyright 2016 by Tutorials Point (I) Pvt. Ltd.

All the content and graphics published in this e-book are the property of Tutorials Point (I) Pvt. Ltd. The user of this e-book is prohibited to reuse, retain, copy, distribute or republish any contents or a part of contents of this e-book in any manner without written consent of the publisher.

We strive to update the contents of our website and tutorials as timely and as precisely as possible, however, the contents may contain inaccuracies or errors. Tutorials Point (I) Pvt. Ltd. provides no guarantee regarding the accuracy, timeliness or completeness of our website or its contents including this tutorial. If you discover any errors on our website or in this tutorial, please notify us at contact@tutorialspoint.com

Table of Contents

About the Tutorial	2
Audiences	2
Prerequisites.....	2
Copyright and Disclaimer	2
Table of Contents	3
1. cPanel – Overview.....	8
cPanel Users	8
Server Administrator –	8
Reseller Accounts –	8
User Account –	8
Why cPanel.....	8
Advantages	9
Disadvantages	9
2. cPanel – Registering a Domain Name.....	10
Importance of a domain	10
Registering a Domain Name	10
3. cPanel – Getting Web Hosting.....	12
Shared Hosting –	12
Virtual Private Servers –	12
Dedicated Server –	12
4. cPanel – Setting Up Nameserver	13
5. cPanel – Logging into cPanel Dashboard	14
6. cPanel – Changing Password	15
7. cPanel – Styles	17
8. cPanel – Contact Information.....	19
9. cPanel Home	21
Sidebar.....	21
Navigation Bar	21
Feature List.....	22
10. cPanel – Statistics & Dashboard	23
cPanel Statistics.....	23
cPanel Dashboard.....	24
11. cPanel – User Manager	25
To Delete an Account	25
To Edit an Account	26
Add a New User.....	28

12. cPanel – File Manager	30
Searching for a File	30
File Manager Settings	31
Working with File Manager	31
Creating a File	31
Creating a Folder	32
Copying.....	32
Moving.....	32
Uploading a File.....	32
Downloading a File	33
Deleting a File or Folder	33
Renaming a File or Folder.....	33
Text Editor	33
Code Editor.....	33
Extracting a File	33
Compressing a File or Folder	33
Viewing a File.....	34
13. cPanel – File Permissions	35
14. cPanel – Images	37
Thumbnailer Converter	37
15. cPanel – Image Scaler	40
16. cPanel – Image Converter	41
17. cPanel – Directory Privacy	42
18. cPanel – Disk Usage	44
19. cPanel – FTP	46
Configure FTP Client	47
Special FTP Accounts	47
20. cPanel – FTP Sessions	48
Terminate a FTP Connection	49
21. cPanel – Backup	50
Full Backup	50
Partial Backups	51
22. cPanel – Backup Wizard	53
23. cPanel – MySQL Databases	55
Create a New Database	55
Add a Database User	56
Modifying a Database.....	57
Check a Database	58
Repair a Database	58
24. cPanel – MySQL Database Wizard	59

25. cPanel – phpMyAdmin	61
Execute an SQL Query	62
26. cPanel – Remote MySQL	63
Add Access Host	63
Remove Access Host.....	64
27. cPanel – Subdomains	65
To Create a Subdomain	65
Managing Redirection	66
28. cPanel – Aliases.....	67
Create an Alias.....	67
Remove Aliases.....	68
29. cPanel – Addon Domain	69
Create an Addon Domain	69
Remove an Addon Domain.....	70
30. cPanel – Redirect.....	71
Permanent (301) Redirect	71
Temporary (302) Redirect	71
Create a Redirect.....	71
31. cPanel – Simple Zone Editor	74
Add an A Record	74
Add a CNAME Record	75
Remove an A or CNAME Record.....	75
32. cPanel – Advance Zone Editor	76
Reset Zone Files.....	76
Add an A record.....	77
Add an AAAA Record	78
Add a CNAME Record	78
Add an SRV Record	79
Add a TXT Record	80
Edit or Delete a DNS Record.....	81
33. cPanel – Email Accounts.....	82
Create an Email Address.....	82
Manage Email Accounts	83
Change Passwords.....	83
Change Quota.....	84
Configure Mail Client.....	84
Delete an Email Account	85
34. cPanel – Email Forwarders	86
Create an Email Forwarder.....	86
Create an Email Account Forwarder	86
Add Domain Forwarder	88
Delete an Email Forwarder.....	89

35. cPanel – Webmail	90
Opening Your Webmail	90
Through cPanel Interface	90
Access webmail directly	92
36. cPanel – MX Entry	93
Configure Email Routing	93
Add an MX Record	95
Edit or Remove an MX Record	95
37. cPanel – Autoresponders	97
Add an Autoresponder	97
Edit or Delete Autoresponder	100
38. cPanel – Track Delivery	101
39. cPanel – Email Filters	104
User Level Filter	104
Create a User Level Filter	104
Edit or Delete a User Level Filter	105
Testing an Email Filter	106
Account Level Filtering	106
40. cPanel – Authentications.....	108
DKIM.....	108
Enabling DKIM	108
Disable DKIM	109
SPF.....	109
Enable SPF	109
Disable SPF	110
41. cPanel – Address Importer	111
Importing Email Addresses.....	111
Importing Email Forwarders.....	113
42. cPanel – Encryption.....	116
Create a GnuPG Key	116
Import a Key	117
Delete or View the Key	118
43. cPanel – Apache Spamassassin.....	119
Enable or Disable Apache Spamassassin	119
Setup Spam Auto-Delete	120
44. cPanel – Visitors.....	121
45. cPanel – Errors	123
46. cPanel – Bandwidth	124
47. cPanel – Webalizer	126

48. cPanel – Raw Access	128
49. cPanel – CPU and Connection Usage	129
50. cPanel – IP Blocker	131
Deny Access to an IP Address or Domain	131
Remove an IP from the Denied List.....	132
51. cPanel – SSH / TLS	133
Generate Private Key.....	133
Upload a Private Key	134
Generate a CSR.....	135
Upload an SSL / TLS Certificate.....	136
Self-Signed Certificate	137
Installing SSL.....	138
52. cPanel – Hotlink Protection	139
Configure Hotlink Protection.....	139
53. cPanel – Ruby on Rails	141
Create a Rewrite.....	142
54. cPanel – Optimize Website	143
55. cPanel – Cron Jobs	145
Setup Cron Job	145
Cron Email	146
Edit or Delete Existing Cron Jobs	146
56. cPanel – Track DNS	147
Domain Lookup	147
Trace Route	148
57. cPanel – Indexes	149
58. cPanel – Error Pages	151
59. cPanel – MIME Types	153
Delete a MIME Type	154
60. cPanel – Virus Scanner	155
61. cPanel – Softaculous Apps Installer	157
Install Application using Softaculous Apps Installer	158
Create Backup of any Application	159
62. cPanel – Installing WordPress	161
63. cPanel – FileZilla FTP Client	166
64. cPanel – CloudFlare	168

1. cPanel – Overview

cPanel is a Linux-based hosting management control panel. It is used to manage your website and server's backend working system. It provides graphical user interface for most of the tasks we perform on the website's server, for example, uploading files, creating emails, setting cron jobs, handling databases, etc.

cPanel Users

cPanel is installed on a Linux system by the server administrator. With the help of the cPanel Software Server, an Administrator can create Virtual Private Servers or it can dedicate the whole server for shared hosting environment. cPanel Shared hosting has three types of user levels.

Server Administrator – This user is the root user of a cPanel Linux Server and has all the permission over the server. Server Admin can create, modify or delete any account from the cPanel Server. The Server Admin has access to cPanel WHM (Web Host Manger), which can be understood as the backend of cPanel.

Reseller Accounts – This user is created by the server administrator and server administrator can choose which type of permissions should be given to reseller accounts. A Reseller account can further create user accounts and has access to all those accounts, which they have created. One reseller account does not have access to the user accounts that were created by another reseller accounts. They also have access to WHM with limited permissions.

User Account – These are normal user accounts, each user who subscribes for a web hosting from a company, is given this type of account. They do not have access to Web Host Manager. User account can host single or multiple websites according to their plans they have purchased from web hosting provider.

Why cPanel

cPanel is packed with many features that is not provided by other web hosting management panels. It is graphical, hence, non-technical users can also use it perfectly. cPanel is responsive to the screen size, hence can be used in mobile and tablets. It will automatically adapt the screen size of the device.

cPanel is very easy to use and configure. It automatically adjusts all the advanced setting for web hosting. A user hardly needs to go to the command line to configure any settings, as it already has all the features inbuilt.

Advantages

cPanel offers the following advantages:

- It is very easy to host a website using cPanel.
- It is multiannual and available in many languages.
- It is responsive and adapts to any screen size, it can be used efficiently in mobile and Tablet too.
- cPanel has in-built File Manager, which helps in managing your files without the hassles of an FTP.
- cPanel has integrated webmail software, which helps in sending and receiving emails through online webmail client.
- You can easily create a backup of your website in a few steps. This will help you to restore your backup, if your website encounters any error.
- You can easily manage your website databases, as cPanel has integrated phpMyAdmin, which helps to directly manage databases.

Disadvantages

cPanel does not have any significant drawbacks, however here are a couple of its notable disadvantages:

- cPanel is a commercial software and you need to pay to get this.
- cPanel is meant for small and medium websites only. Creating a large website using cPanel is not recommended.

2. cPanel – Registering a Domain Name

If you have a website developed locally or you have planned to make a website, then there are two things that you will need – a **Domain Name** and **Web Hosting**. A Domain name is the address of your website, which will be used by your users to access it. For example, **tutorialspoint.com** or google.com these are domain names.

A domain name has two parts, TLD (Top Level Domain) and SLD (Second level domain), for example in **tutorialspoint.com**, tutorialspoint is second level domain of TLD .com, or you can say it's a subdomain of .com TLD. There are many top level domains available, like .com, .net, etc. and also country specified TLD like .in, .uk, .ae, etc.

Importance of a domain

Getting a domain name of your choice can be very useful. You can use it for many reasons, for instance, you can create the identity of your brand online or you can create a personal blogging website. If you have a business, people will be able to learn about your business remotely.

Registering a Domain Name

Domain names are registered with a non-profit organization ICANN. It does not let you register your domain directly, but you will have to go with a domain registrar for this purpose. Domain name registrations involve a registration fee for a year, and you have to renew the domain every year by providing a renewal fee. Domain names cannot be purchased permanently at once, but you have to renew it every year, if you fail to renew the domain, it is automatically deleted from registry.

If you want to register your domain name, then you will have to follow these steps:

Step (1) – Choose a **perfect domain name** for your website. If it's a business website, then you may want to go with a domain name, which is the name of your business.

Step (2) – Choose a **good domain registrar company** having good support infrastructure. For example, GoDaddy or BigRock.

Step (3) – In the registrar's website, **check if your domain name is available** for registration. If the domain you selected has been already registered by someone, then you will have to think of some other domain name. If your domain name is available to register, then you can proceed further.

Step (4) – Provide your contact information and everything that the registrar asked for. It is **mandatory** that you provide correct information while registering

a domain name, as it will be visible to everyone if the user looks for **WHOIS** information.

Step (5) – You can hide your contact details by choosing to be viewed by anyone by subscribing **privacy protection service**. This service hides all your contact information to everyone except the registrar, this service is provided by many domain registrars at some extra cost.

Step (6) – Complete the purchase by **paying the registration fees**. Domain name will be registered to you.

3. cPanel – Getting Web Hosting

If you have already registered your domain name, the next step is to get a web hosting for your website. Web hosting is a service, which provides space for your website on internet. If you want your website to publish online, then you will have to get web hosting service.

In a web hosting service, your website is stored in high powered computers called web servers, which are connected to a high speed network and they are powered-on 24/7. While purchasing a web hosting service, you rent a space for your website on these servers.

There are basically three types of web hosting –

Shared Hosting – In this type of web hosting, a single server hosts multiple websites, sometimes thousands of them. Each account on this server has certain limits on using disk space to store websites, databases and bandwidth. This is the amount of data transferred through your website. This type of hosting is cheap and suitable for small and medium websites.

Virtual Private Servers – In this type of hosting, a Linux Server is divided into several parts and each part acts as a different server, each server has some limited resources given. In this, the VPS administrator has root access to his VPS and can then host single or many websites according to his need. These type of hosting is recommended for medium and large websites. Cost of VPS is higher than Shared Hosting, but lower than Dedicated Hosting.

Dedicated Server – In this type of hosting, a whole server is rented to the user, who can host a large website on this server or can use it to host multiple websites in this server, the server admin can create multiple VPS. Cost of dedicated hosting is much higher and it requires a server admin to manage this type of hosting.

If your website is new and it is not expecting much resource usage, then you can go for shared hosting. You can purchase shared hosting for hosting one website or multiple websites according to your need. In this tutorial, we will learn about hosting a website using cPanel, hence it is recommended that you purchase the hosting that comes with cPanel.

4. cPanel – Setting Up Nameserver

When you have purchased your hosting, you will have to connect your domain with the hosting that you have purchased. If you have purchased the domain and hosting from the same provider, then it is liable that your Nameservers are already setup. If you have purchased your domain and hosting from different providers, then you will have to manually add new Nameservers to your domain, so that it can point your domain to the right server.

Nameservers are a part of Domain Name System. These DNS servers keep the records of which domain is connected to which IP address. Nameservers allow us to use a domain instead of IP address of the DNS server. When a visitor types the URL of your domain then the DNS server tells the browser that from which server it should load content from. In easy words, Nameservers define the current DNS provider of your domain.

When you get the email of the Login details of your web hosting server along with it, you also get the details of your Nameservers. Most hosting providers use their own DNS servers. For setting up your Nameservers, you will have to login to your domain control panel, and update your Nameservers by replacing the old one. Each domain provider has its own application to do so, you will have to refer to your domain registrar's documentation for further details.

Domain Nameservers take time to propagate through different DNS servers around the globe, the change may reflect instantly or it may take up to 48 hours of time according to the DNS servers of hosting provider.

5. cPanel – Logging into cPanel Dashboard

In this chapter, we will learn to login into the cPanel Dashboard. For logging into the dashboard, you will need your login credentials. This information is sent to you, when you have signed up for cPanel hosting or you may have created during purchase of hosting.

cPanel Dashboard is accessible by two ports – 2082 for unsecured connections and 2083 for secured connection, many hosting providers support unsecured connections, but it is always recommended that you should use a secured connection only.


There are many ways to find the login screen of a cPanel. Recommended is that you may use the IP address of your cPanel, you may find the cPanel using IP address by typing the following in address bar –

```
https://<your_IP_address>:2083  
https://<your_IP_address>/cpanel
```

If you have already updated your Nameservers for your domain, then you may use your domain for directly accessing cPanel by your domain. You may find cPanel login screen using your domain by typing the following into the address bar –

```
https://<your_domain>:2083  
https://<your_domain>/cpanel
```

Once you are redirected to your login screen, you will find the login screen like shown below.




You can enter the Username and Password and press the **Log in** button to login into the cPanel Dashboard.

6. cPanel – Changing Password


When you are successfully logged into a cPanel Dashboard, first and foremost, change the password of your cPanel account. This is very important, so that the security of cPanel remains intact. Nobody would want their website to be hacked.

To change your cPanel Password, follow these steps:

Step (1) – In cPanel Home, click **username** written over the right corner of the dashboard.



Step (2) – Click **Password & Security** option. You will find Change Password Interface.



Step (3) – Write your **old password** and in the following fields, write your new password twice.

Change Password

Change your account password below. Password strength is important in web hosting; we strongly recommend using the Password Generator to create your password. Follow the tips below to keep your password safe.

Old Password

New Password

New Password (Again):

Strength (Why?)

Enable Digest Authentication ⓘ

Step (4) – Enable **digest authentication** option if you need to access your webdisk via an unencrypted connection in windows machine. This type of connection is unsecured and not recommended.


Step (5) – Click **Change your password now!** Button to change your current password. If successful, then cPanel will automatically log you out and you will have to login again with your new password.

7. cPanel – Styles


You can change cPanel’s look and feel using this interface. cPanel has two major interface styles in which you can manage your web hosting. Although these interface is very standard, but these can be modified by your server administrator or reseller account admin to change its logo and icons etc.

To modify your cPanel Style follow these steps:

Step (1) – In cPanel Home click username written over the right corner of your dashboard.




Step (2) – Click Change Style option. You will find Change Style Interface.




Change Style

Choose a style to customize your cPanel interface. For more information, read the [documentation](#).

Basic Current



Retro Apply



Step (3) – Choose any style option from the available styles, click Apply button which can be found over the top of the style to load the new style.

Choose a style to customize your cPanel interface. For more information, read the [documentation](#).

i Applying styles and reloading the page.

Basic Current

Retro Apply


Step (4) – cPanel will automatically reload to apply the new setting and you will find a new interface according to the one you selected.

8. cPanel – Contact Information


In this interface of cPanel, you are allowed to change the system email address. It is the email address on which the system can notify you for important updates. You cannot use your system email address or any email address, which is connected with your domain, so that you do not lose any important update, when the system is down.


To update your contact email, follow these steps:

Step (1) – In cPanel Home, click username on the right corner of your dashboard.



Step (2) – Click on Contact Information option. You will find Contact Information Interface.





Contact Information

This is an email address at which the system can contact you. This should be an email address that is not on your account.

✔

If you wish to provide a second email address to receive notifications, enter it here.

An access token for Pushbullet.

Contact Preferences
 Notify me when:

My contact email address changes.

Step (3) – Enter the email address on which you want the system to contact you for important notifications.

Step (4) – You can enter a second email address on which you can receive the copy of that email sent on your primary email.

Step (5) – You can choose the options of an event on which the system should send you notification in contact preference. It is recommended that you leave every checkbox selected.

Contact Preferences
 Notify me when:

My contact email address changes.
 The system will notify you at your current and previous contact email addresses.

My preference for contact email address change notifications is disabled.

My account approaches its disk quota.

Any of my account's email accounts approaches or is over quota.


My account's password changes.
 My preference for account password change notifications is disabled.

An external account links to my account for authentication.
 My preference for external account link notifications is disabled.

Step (6) – Click the Save button to save your contact preference.

9. cPanel Home

Once you are logged into cPanel dashboard, you will see that it has so many options. In this chapter, you will find a quick brief of every option shown in the cPanel dashboard.



Sidebar

You can switch to your accounts' four main areas of cPanel through this interface, which are –

- **Home** – This is where you can access all the features of cPanel.
- **Statistics** – Displays information about your cPanel account and also the resources it used.
- **Dashboard** – Displays quick links to change styles etc. and overview of your cPanel account.
- **User manager** – Here you can manage the users of your cPanel account.

Navigation Bar

On this toolbar, you will find the cPanel's logo and a search box in which you can type any function of cPanel to access it quickly. Like your User account name and some quick links, once you click on it. The Notification Icon will show you the recent notifications about your cPanel account. Logout button will end your session (log you out) from the cPanel.

Feature List


It displays all the features and functions you have in your cPanel. You can click on any function and it will take you over to the desired functions interface.

10. cPanel – Statistics & Dashboard

In this chapter, we will discuss about the cPanel statistics and the dashboard along with a few examples and screenshots for better understanding.

cPanel Statistics

The statistics interface of cPanel shows quick statistics of your cPanel account. It includes several types of information shown below. To view quick statistics of your cPanel account, click on second icon statistics from sidebar at left. You will find this information in cPanel quick statistics.




General – It will show you the amount of bandwidth allotted to your account and also the amount of bandwidth, which is used by you. It will also show you the FTP accounts available in your cPanel account. It will also show the information of your Home directory and the IP address, from which you logged in last time. You can click on the Server Information to view the detailed information of your server.

Domain Info – In the next box, it will show you the information of main domain and the number of add-on domains, subdomains and aliases you have created.

Mail Info – This section will show the information about your emails. It will tell you how many email accounts, Autoresponder Forwarders and Filters you have created along with the total number of resource allotted.

Disk Space – In this section, the total disk space of your account is shown and also the amount of space used by MySQL database is shown along with total amount of space allotted to your account and MySQL database.

Database – This section shows the info of total number of databases you have created along with the total number of database you can create.



System Information – In this section, the statistics cPanel shows you the information of your system with total CPU usage, virtual and physical memory that is being used. It also displays information of the process you are running, the Input and Output uses and also it displays number of inodes, which means the number of files.

cPanel Dashboard

Through this interface you can see some brief statistics of your cPanel account plus you can change the theme of your cPanel account. To access your dashboard, you can click on the third icon 'Dashboard' on the left sidebar.

The screenshot shows the cPanel dashboard with the following elements:

- QUICK LINKS:** File Manager (highlighted with a red arrow), Addon Domains, Email Accounts, MySQL® Databases, FTP Accounts.
- SWITCH THEME:** A dropdown menu currently showing 'paper_lantern'.
- USED 5.78 MB / LIMIT 100 GB:** A progress bar for disk usage.
- USED 0 BYTES / LIMIT 1,000 GB:** A progress bar for bandwidth usage.
- MAIL STATISTICS:** A progress bar for email accounts, showing 4/100.
- DATABASE STATISTICS:** A progress bar for MySQL® Databases, showing 2/100.

The footer includes the cPanel logo (54.0.12) and links for Home, Trademarks, and Documentation.


11. cPanel – User Manager

This is a new feature introduced in the latest edition of cPanel. Through this user manager section, you can control all the users you have in your cPanel with a single interface. This interface will show you all the user accounts, who have email accounts or FTP accounts that are associated with your domain. You can delete edit those accounts, change passwords and also you can delete them from here. This interface gives you the ability to add new user and associate them to FTP and Email account too.

To Delete an Account


To use user manager and delete user accounts, you can follow these steps:

Step (1) – Open User manager by clicking the last icon in the sidebar on the left side. Once user manager is open, you will see an interface like this –



Step (2) – You can view all the accounts of your cPanel here, which includes your system accounts too. Account having the Inbox icon colored shows that the account has an email address. The accounts having the truck icon colored show that the account has an access to FTP account, whereas the accounts having the disk icon colored shows that the account has access to a webdisk.

Step (3) – Find the account you wish to delete and click on the delete link under the domain.




Step (4) – You will be asked for confirmation, click on the delete button to delete the user account.

To Edit an Account


If you wish to edit an account or to change the password of any account. Follow these steps:

Step (1) – Choose the account you wish to edit or change password of, from the user manager. Click on Edit link or Change Password link under that account. Both of these will take you to the same interface, where you can edit the account.

The "User Manager" interface for editing a user. At the top left is a logo with three green figures and the text "User Manager". Below it is a breadcrumb trail: "User Manager / Edit User". The main section is titled "Basic Information" and contains four input fields: "Full Name" with the value "John S. Doe", "Username" with the value "info" and an "@" symbol to its right, "Domain" with the value "tutorialspoint.com", and "Alternate Email" with a help icon and the value "alt.email@another.domain.tld".

Step (2) – You can specify the Full name of the user. Or else, you can provide alternate email id for that account.

Step (3) – Scroll down to see the Security Information, you can provide a new password in this interface or whether, you wish to change the password, if not leave it blank.




Security Information

Password

Enter Password

Password (Again)

Step (4) – Choose the services you want to enable for that user account from the services interface.



Services

Email Enabled

Quota

Unrestricted

MB

FTP Disabled

Quota

Unrestricted

MB

Home Directory

You can enable or disable email, also you can change the Quota for the email of that account. You can also enable FTP for that account, just move the switch to enable the FTP account.

Step (5) – Click Save for saving the settings for that existing user.

Add a New User

You can also add a new user and give him access to email and FTP. To create a new user, follow these steps:

Step (1) – Click 'Add User' Button found on the right side of the user manager interface. And you will see the same screen, which you saw on the Edit user interface.

Basic Information

Full Name

Username *
 @

Domain

Alternate Email [?](#)

Security Information

Password *

Confirm Password *

Step (2) – Provide all necessary information like username and password, you can also provide full name of the user, but it is optional.

Step (3) – Choose services you want to give to that particular user. Enable the services by moving the switch to enable or disable the services.

Services

Email Enabled <input checked="" type="checkbox"/>	FTP Enabled <input checked="" type="checkbox"/>
Quota <input type="radio"/> Unrestricted <input checked="" type="radio"/> 250 MB	Quota <input checked="" type="radio"/> Unrestricted <input type="radio"/> [] MB
	Home Directory public_html/tutorialspoint.com/new


Create Create and Add Another Cancel

Step (4) – Click the Create button to create the user and return to the user manager interface or click Create and Add Another to create the user and return to Add user interface to add a new user again.


12. cPanel – File Manager

cPanel File Manager gives you useful options to quickly manage your files within the cPanel interface. It's easy to use and it removes the hassles of using FTP. You can create, upload, modify or remove files from this interface. It also gives the feature of moving files to Trash before permanently deleting them, from which it can be recovered later.

To open the file manager, click on File Manager in the Files section.



It will open a new tab and once you are in File Manager, you will see a Dashboard like this.



cPanel File Manager gives you a lot of flexibility for Navigating within your files.

You can use file manager for following tasks.


Searching for a File

To search for a file, use the search bar on top of the File Manager Dashboard. You can search within all your files, public_html or current directory, then write the file name in next input box and click go to search for a file.

Note: *public_html* is folder in cPanel, all the files which are accessible from the frontend of your website are stored in this directory. *Index.html* or *index.php* found in this folder loads first, when somebody accesses your website from frontend by your URL.

File Manager Settings

To access cPanel File Manager Preferences, click setting buttons from the top of the Dashboard. You will see a Prompt as shown below.



- By default, cPanel File manager opens the Home Directory of your account, when opening the cPanel. But, we can override this by choosing it with Web Root, which is public_html folder of Public FTP root or with a Document root of your domain or any subdomain you create.
- In Linux, hidden files have a single Dot (.) in front of them. The default cPanel File Manager does not display them, but you can choose to show hidden files by enabling Show Hidden Files (dotfiles) option.
- When we open a text file, which may be HTML, PHP or Plain Text file, cPanel opens a dialog to check the character encoding of the file, to ensure maximum compatibility, when editing the file. You can disable this feature by selecting – Disable Character Encoding Verification Dialogs.

Working with File Manager

Creating a File

To create a new File, navigate to the directory, where the file needs to be created and then click New File from the Dashboard. A prompt opens and asks you the file name. Enter it accordingly with the extension of file and Path, where the file will be created. Finally, click Create New File and a new file will be created.

Creating a Folder

To create a new Folder or Directory, navigate to the directory in which you want to create the folder. Click on New Folder from the Dashboard. A Prompt will be opened to ask you name of your New Folder. Enter your desired Folder name and Click Create New Folder. Your new folder will be created.

Copying

You can copy a single file or folder or even multiple files or folders. To copy a single file or folder select what you want to copy with a single mouse click over the it and Click Copy. You will be asked the file path where you wish to copy the file or folder to, enter the Path accordingly and click Copy File(s).

To copy multiple files or folders, single click on the desired files or folders by holding down the ctrl key to select multiple files or folder and then click on copy. Enter the desired location and Click to Copy File(s) button to copy multiple files.


Moving

You can move a single file or folder or multiple ones. To move a single file or folder, select the one that you want to move with a single mouse click over it and Click on Move. You will be asked the file path where you wish to move the file or folder to, enter the Path accordingly and click on Move File(s).

To move multiple files or folders, single click on the desired files or folders by holding down the ctrl key to select multiple files or folder and then click on move. Enter the desired location and Click to Move File(s) button to move multiple files.

Uploading a File

To upload a file from the cPanel File Manager Interface, navigate to the directory in which you wish to upload and then, click Upload. You will find the interface shown below.



You can Drag and Drop the file to upload or you can select the file from Select File button. If you want the File Manager to automatically overwrite the files with same name, you can select – **Overwrite existing files** checkbox.

Downloading a File

To download a file from the cPanel File Manager, you can select the single file or multiple files with single click on file name, and click over Download to download the files.

Deleting a File or Folder

To delete Single or Multiple file or folder just select the files with single mouse click and click on Delete button. You will get a prompt for sending the files into Trash, if you want to permanently delete the files then select Skip the Trash checkbox. If the check box is not selected, files are moved to Trash Folder from where you can recover them later.

Renaming a File or Folder

To rename a File or Folder, select the file or folder with a single mouse click and Click on rename. You will get a prompt to enter new file or folder name. Enter file or folder name accordingly and click on Rename File button to save. You can also double click on Name of any File or Folder to rename the file.

Text Editor

To edit any text file with simple text editor, select the file and click on Edit button. You will get a prompt with Encoding check if enabled, then click on Edit in prompt to edit the file. Text editor will open in a new tab, where you can edit the file. You can also switch to Code editor from here. When you have finished editing, click Save to save the File.

Code Editor

Code editor makes it easy to edit those files, which contains code in them. It differentiates color between codes, which makes it easy to edit those files.

Extracting a File

To extract a File which are compressed, select the file you wish to extract and click on Extract Button. You will get a prompt to enter the path where you wish to extract the files, if you enter a path which is not existing, cPanel File Manager will create the directory and extract the file in it.

Note: cPanel File Manager can only extract files which are in Zip, GZip and BZip2 type of compression.

Compressing a File or Folder

To compress a folder or a single or multiple files, select the files and click on Compress. You will get a prompt, select the compression method where you can choose from Zip, Gzip or Bzip2. It will ask you to enter the file name, enter file name accordingly and click Compress File(s). After compression, the result will be shown to you.

Viewing a File

This option helps you to view the content of known file types within cPanel Interface. Select the file you wish to view and click on View. It will open a new tab and the content of file will be shown to you.

13. cPanel – File Permissions

All files and directories in Linux Operating System has access permissions. This feature gives the ability to the user for setting up different access levels for each user and also Operating system gets the ability to deal with different request for accessing the file. This feature makes system more secure to potential security threats. There are three types of access permissions:

- **Read:** It is denoted by 'r' and number 4, it gives ability to the user for reading the file only.
- **Write:** It is denoted by 'w' and number 2, it gives ability to the user for writing into the file only.
- **Execute:** It is denoted by 'x' and number 1, it gives ability to user for executing the file only.

Access permissions can be given in groups too, for example, if we want to give a file to read and write permission only, we can assign 'rw-' to that file or in numerical form, we can assign number 6 – as 4 for read and 2 for write equals to 6.

These access permissions are given to three types of users:

- **User:** It is owner of the file.
- **Group:** It is the group of users in which Owner lies.
- **World:** It is referred to everyone else.


We give access permissions according to file types in cPanel. By default, cPanel File Manager gives 6-4-4 permissions to the users – 6 to the User, 4 to the Group and 4 to the World. Most of the time we do not need to change the file permissions unless needed.

You can change the file permissions in cPanel environment by using the following steps:

Step (1) – Go to File Manager from cPanel Home.

Step (2) – Navigate to the File or Folder you wish to change permissions to and select the file or folder by a single click of the mouse.


Step (3) – Click on Permissions link from the Top menu of File Manager and you will get a Prompt as shown below.




Step (4) – Choose permissions according to your need and Click on Change Permissions to save the new access permissions of the file.

14. cPanel – Images

With this feature of cPanel, you can manage and modify your Images directly through its Interface. The image must be uploaded into your account to use this feature. To access cPanel Images, click Images Link found on your files section.




This feature includes the following tools –



Thumbnailer Converter

Thumbnailer creates small images or Thumbnails of the original image. This is done by using these images wherever required as it could save more bandwidth. For example, when we need to display a preview of the photo, which will then be opened into a new tab, when the user clicks preview image. We can use a small image here, rather than forcefully scaling the image to display in a small size.





















To use **Thumbnailer converter**, we can open the application by clicking on the **Thumbnailer** link from images section. We will get a similar dashboard as shown below.



Images Thumbnailer

Select a folder to thumbnail.

Click on a **folder icon** to navigate. Click on a **folder name** to select it.


	/ (Current Folder)	
	.cagefs	771
	.cl.selector	755
	.cpanel	700
	.cphorde	700
	.htpasswd	750
	.pki	740
	.softaculous	711
	.trash	700
	access-logs	750
	etc	750
	logs	700
	mail	750
	public_ftp	750
	public_html	750
	softaculous_backups	711
	ssl	755
	tmp	755
	www	750
	.bash_logout	0644

Step (1) – Navigate to the desired directory from which you wish to create Thumbnails, to navigate within directories use folder icon on left hand side.

Step (2) – Select folder from which you wish to create thumbnails, by clicking on the name of folder displayed in middle.

Note: Thumbnailer is a bulk thumbnails creator tool, single image cannot be used in these tools.

Step (3) – In Scale Percent, text inputs enter the percentage by which you wish to shrink the image. Select Keep aspect ratio to maintain original proportion of the Image.



Images Thumbnailer

We will be thumbnailing images in `"/home/liptan/public_html"`.

Scale Percent:

25 % × 25 %

Keep Aspect Ratio

Thumbnail Images **Reset Dimensions**

Step (4) – Finally click on Thumbnail Images to create thumbnails.

The system will automatically create a subfolder, Thumbnails into selected folder and all files in that folder will be converted and saved there with a prefix **tn_**. For example, if you have an image abc.png, then it will be saved into tn_abc.png.

15. cPanel – Image Scaler

Image Scaler is a very useful tool to scale an Image to increase or decrease its dimensions, or we can say to resize an Image. To scale an image, we need to follow these steps:


Step (1) – Open Image Scaler by clicking **Scaler** from Images section.

Step (2) – Navigate to the directories by clicking on folder icon on the left hand side, same way as done above.

Step (3) – Select the File which you want to resize by clicking on the Name of File.

Note: Image Scaler is a single image tool, and can be used with a single image at a Time.

Step (4) – Enter either new dimensions in Pixels or Enter Percentage by which you want to increase or decrease the Image. You can select, Keep Aspect Ratio, so that the Image ratio is not disturbed, and also you can retain the old copy of the file as Image Scaler replaces old Image to the new one.



Images Scaler

We will be scaling "/home/liptanxy/public_html/dhirubhai-ambani.jpg".
Current Dimensions: /home/liptanxy/public_html/dhirubhai-ambani.jpg JPEG 300x250 300x250+0+0 8-bit sRGB 11.2KB 0.000u 0:00.000

New Dimensions:

150 x 125

Percent

50 % x 50 %

Keep Aspect Ratio

dhirubhai-ambani.jpg
File Type: JPEG image data, JFIF standard 1.02

Retain a copy of the old image as:
/home/liptanxy/public_html/old-dhirubhai-ambani.jpg

Scale Image Reset Dimensions

Step (5) – Finally Click Scale Image.

16. cPanel – Image Converter

Image converter can be used for converting image format of any image. It can convert from one supported type to any other supported type. To use Image converter, open the interface by clicking **Converter** link from Images section.

Step (1) – Navigate to the directories by clicking on folder icon on the left hand side, as we did above.

Step (2) – Select the File or Folder which you want to resize by clicking on the Name of File or Folder.

Note: Image Converter can be used with a single file or folder.

Step (3) – Select new file type from the prompt as shown below, which can be:

- Portable Network Graphics (.PNG)
- JPEG (.JPG)
- GIF (.GIF)
- Bitmap (.BMP)




Step (4) – Finally Click on Convert to convert the file type.

17. cPanel – Directory Privacy


This feature of cPanel allows us to protect certain directories with a username and password. If a directory is protected by this, then if somebody from the front end of your website tries to access the file, they will be prompted to provide a username and password, if username or password does not match, then the user will not be able to see the content of that directory.

To configure a password for a directory, use the following steps:

Step (1) – Open Directory Privacy Configuration by clicking **Directory Privacy** in the Files Section.



Step (2) – Navigate within your directories to find the directory you want to protect. Use icon on the left hand side to open a directory.



Step (3) – Select the directory you want to protect by clicking on the name of the folder, you will get same configuration as shown below.

Step (4) – Select Password protect for this directory checkbox and enter a Label which you wish to display in the frontend, click **Save** to protect this directory.

Step (5) – To give access to users, you will need to create users. Enter username and password to create a new user, who will have access to this directory from the frontend.

Step (6) – Click Save to give access to this user. You can also create more than one user here.

If you now try to access your password protected directory, you will get a prompt like this –


You can now enter the username and password to access this directory.

18. cPanel – Disk Usage


cPanel Disk Usage is a very efficient way to monitor your accounts available and use disk spaces. This feature scans your disk to provide you a graphical overview of the Disk usage. It displays disk space used by directories, but it does not show how much space is consumed by an individual file. It also displays information of disk quota used by MySQL Databases, hidden directories and Emails.

It helps in management of disk quota, because once you know which directory has the largest files, you can navigate to that directory using file manager and delete unnecessary files.


To access this feature, click Disk Usage link from Files section of cPanel.



cPanel Disk Manger has mainly **two tables**. The **first table** gives you information about disk space used by subdirectories of home directory and space used by other features like MySQL, Mailing Lists. Please refer to screenshot below.



The **Second Table** displays a directory structure, which has all the subdirectories including hidden ones, to open a directory to view space used by that subdirectory, you can click on the arrow shown in front of the name of the directory. Clicking on the name of directory will take you to the File Manager. In this table, you can see which subdirectory has the largest files in them, it is very helpful when there are lots of directories in your account.

Sort directories by: <input type="radio"/> Name <input checked="" type="radio"/> Disk Usage		
Directory	Contained Disk Usage	
	MB	Bytes
 /	0.82	856064
> .cphorde	0.45	471040
> .cpanel	0.13	131072
> mail	0.06	61440
√ public_html	0.04	45056
protected	0.00	4096
cgi-bin	0.00	0
> .ssh	0.02	24576
> .htpasswd	0.01	12288
> .softaculous	0.01	12288
> tmp	0.01	8192
.cl.selector	0.00	4096
etc	0.00	4096
> public_ftp	0.00	4096
.trash	0.00	0
www	0.00	0


cPanel 11.52.2.4

19. cPanel – FTP


File Transfer Protocol (FTP) allows you to manage your files with third party applications like FileZilla, CoreFTP, etc. Using a FTP file manager to upload files is a great practice when the number of files or size of the files is large. FTP accounts configures users who can upload, download or modify your files through FTP. Each FTP user has his own username and home directory, only that certain directory the user will have access to.

To create an FTP account, please follow these steps:

Step (1) – Open FTP accounts feature by clicking FTP accounts found under Files Section.



Once FTP accounts feature is opened, you will see the following screen.

A screenshot of the 'FTP Accounts' configuration page in cPanel. The page title is 'FTP Accounts' with a truck icon. Below the title is a brief description: 'Add and configure FTP Accounts to get your website on the internet fast. FTP allows you to manage the files that are associated with FileZilla. For more information, read the documentation.' The main section is 'Add FTP Account'. It contains a 'Log In' field with 'user1' and '@liptan.xyz' as a suffix. Below that are 'Password' and 'Password (Again)' fields, both masked with dots. A 'Strength' indicator shows a green bar for 'Very Strong (100/100)' and a 'Password Generator' button. The 'Directory' field is set to '/home/liptanxy/public_html/user1'. The 'Quota' section has radio buttons for '2000 MB' and 'Unlimited', with 'Unlimited' selected. A 'Create FTP Account' button is at the bottom.

Step (2) – Enter Log in name for your new user, it will be the user's username, also provide a strong password for this user.

Step (3) – Enter Directory for your new user, you may also leave it with pre-filled directory name according to your user.

Step (4) – Provide FTP storage quota, you may provide unlimited quota or use some value in Megabytes.

Step (5) – Click on Create FTP Account and Your FTP account will be created.

Configure FTP Client

To configure your FTP client, you can download any pre-built configuration file by clicking **Configure FTP Account**.

You can download FTP Configuration files for FileZilla or CoreFTP, which are windows software or Cyberduck for Mac.

Special FTP Accounts


These FTP accounts are pre-built with hosting account and cannot be deleted, these are used for administrative purposes.

One of the Special FTP account is your Administrative FTP account, whose username will be same as your accounts username. This FTP account's home directory is your cPanel accounts root directory. You can access all the files of your account with this FTP account. Its password will be the same as your cPanel account password.


20. cPanel – FTP Sessions

The cPanel FTP Session interface shows current users, which are logged in to website through FTP. This interface is helpful and it helps you to terminate unwanted connections with one click.

To access this feature, click FTP Sessions link from the Files section of cPanel.



It will open an interface in which it will show the current users who are logged into your site. If no user has logged in, it will display the message that no users have logged in.




Here it will show the following information:

		Example
User	Displays username of logged in user	liptanxy
Logged in Form	Displays IP address or hostname of user's system	106.215.178.204
Login Time	Displays Login Time of User	Thu Jan 21 13:50:03 2016
Status	Displays Sessions status	IDLE
Process ID	System's FTP Session Process ID	203299
Actions	Terminate the connection	Disconnect

Terminate a FTP Connection

If you think that any user is not doing any activity and is in IDLE mode for a long time, or if you think a user is uploading a very large file, or doing something malicious, you can terminate the connection by clicking the disconnect button from **Actions**. You will see the following prompt.



Click on Disconnect "User", and user's FTP connection will be terminated instantly.

21. cPanel – Backup

This feature of cPanel is very useful for your website. We can use backup feature for transferring our website to the new host. If we are making a change in the website files or database, we can create a backup of website. So that, if in future anything wrong happens to the website while editing, we can always restore to as it was before. If any problem occurs with the hosting provider, you will always have a copy of the website.

cPanel Backup creates a zipped copy of your entire website or a part of your website. There are two types of Backup in your cPanel Backups.


Full Backup

Full Backup creates a zipped copy of your entire website and cPanel account. It includes all the files you own or you have access to. It also includes all the databases, email accounts, email lists, subdomain, etc.


Full Backups **cannot** be restored through cPanel interface. It is only used when you are transferring your current host to the new host. You need to upload this zipped backup into your home directory and ask your hosting provider to restore it.

To download your full website backup, please follow these steps:

Step (1) – Open cPanel Backup by clicking **Backup** from the Files section in cPanel Home.



At the top, you will find Full Backup as shown below –



Step (2) – Click on the Big Blue button on which “Download a Full Website Backup” is written and you will be taken to this screen.

Backup

A full backup will create an archive of all the files and configurations on your website. You can only use this to move your account to another server, or to keep a local copy of your files. You **cannot** restore full backups through your cPanel interface.

Backups Available for Download:

Generate a Full Backup

Backup Destination

Home Directory

Email Address

liptanbiswas@gmail.com

Do not send email notification of backup completion.

Step (3) – Select Backup destination, leave it as home directory. This will create a backup in your home directory, from where you can download it later. Enter the email address, where you want to receive a notification, when full backup of your website is ready to be downloaded. As full website backup takes time to generate.

Step (4) – Click **Generate Backup** and you will see a success message of Backup in Progress.

To download the Full Website Backup, you can always come back to this page after you receive your email notification and you will see a screen similar to the one shown below.

Backup

A full backup will create an archive of all the files and configurations on your website. You can only use this to move your account to another server, or to keep a local copy of your files. You **cannot** restore full backups through your cPanel interface.

Backups Available for Download:

[backup-1.22.2016_06-41-23_liptanxy.tar.gz](#) (Fri Jan 22 06:41:23 2016)

Download your backup by clicking over the backup link.

Partial Backups

Partial backup is created and can be downloaded instantly. Through Partial Backup, you can download your Home Directory, Databases, Email Forwarders and Email Filters separately. You can restore the downloaded backups any time by uploading them to cPanel using the same interface.

To use this feature, open your Backup section using the same method used above in Step 1, scroll down and you will see a similar interface shown here, interface will vary according to your domain and data.

Partial Backups

<p>Download a Home Directory Backup</p> <p>Home Directory</p>	<p>Restore a Home Directory Backup</p> <p><input type="button" value="Browse..."/> No file selected.</p> <p><input type="button" value="Upload"/></p>
<p>Download a MySQL Database Backup</p> <p>Databases</p> <hr/> <p>liptanxy_WP1</p> <hr/> <p>liptanxy_WP2</p>	<p>Restore a MySQL Database Backup</p> <p><input type="button" value="Browse..."/> No file selected.</p> <p><input type="button" value="Upload"/></p>
<p>Download Email Forwarders</p> <p>Forwarders</p> <hr/> <p>liptan.xyz</p>	<p>Restore Email Forwarders</p> <p><input type="button" value="Browse..."/> No file selected.</p> <p><input type="button" value="Upload"/></p>
<p>Download Email Filters</p> <p>System Filter Info</p> <hr/>	<p>Restore Email Filters</p> <p><input type="button" value="Browse..."/> No file selected.</p> <p><input type="button" value="Upload"/></p>


You can click **Home Directory** button to download your home directory backup. To restore your home directory, you can upload the same file in the right hand side interface on which *Restore a Home Directory Backup* is written.

You can do the same with Databases, Email Forwarders and Email Filters.


22. cPanel – Backup Wizard

You can use cPanel Backup Wizard to Backup and Restore your cPanel website step by step. cPanel Backup wizard is created for non-advanced users to simplify the backup and restore process.

To use cPanel Backup Wizard, open this interface by clicking the Backup Wizard link, which can be found under the Files section of the cPanel Home.



Once you are inside your Backup Wizard you can Create Backups or Restore Backups through the similar Interface shown below –



To use this Backup Wizard, there are 3 important steps:

If you need to download backup of your website

Step (1) – Select Backup.

Step (2) – Select Full or Partial backup, as stated in the previous chapter. We cannot restore Full Backup, same applies here too. If you wish to download Partial Backup, you can click on any one from the Home Directory, MySQL Databases or Email Forwards & Filters. Partial Backup downloaded from Backup Wizards can be restored through the Backup Wizard only.

Steps:

① Backup/Restore	② Full or Partial Backup	③ Download
------------------	---------------------------------	------------

Full Backup

This feature allows you to create an archive of all the files and configurations on your website.

[Full Backup](#)

Note: You can only use this to move your account to another server, or to keep a local copy of your files. You cannot restore Full Backups through your cPanel interface. Find out more details on the above link.

Select Partial Backup

This feature allows you to select which partial backup you want to download.

[Home Directory](#)
[MySQL Databases](#)
[Email Forwarders & Filters](#)

Step (3) – Download your backup according to your choice.

If you need to restore your website form the backup you downloaded, follow these steps:

Step (1) – Select Restore from Backup Wizard Interface.

Step (2) – Select Restore Type from Home Directory, MySQL Databases or Email Forwarders & Filters.

Steps:

① Backup/Restore	② Select Restore Type	③ Restore
------------------	------------------------------	-----------

Select Restore Type

This feature allows you to select what to restore.

[Home Directory](#)
[MySQL Databases](#)
[Email Forwarders & Filters](#)

Step (3) – Upload your backup file to and click on Restore Button to restore your backup.

Steps:

① Backup/Restore	② Select Restore Type	③ Restore
------------------	-----------------------	------------------

Final Step

Restore your backup.

Restore a MySQL Database Backup

No file selected.


[Upload](#)

23. cPanel – MySQL Databases

MySQL is the most popular Open Source SQL Database management system. To manage a huge volume of data efficiently, we store the data in tables, a group of many tables can be created in a single database. This interface allows you to create and manage the existing MySQL databases.


If you are creating a PHP based application or any application that uses a database, then you will need to create a database and a database user to access this database. To use WordPress, Drupal, Joomla or any other CMS, you will need to create a MySQL database before installing these CMS.

To create a new MySQL database, you need to open MySQL interface by clicking MySQL Databases link, which can be found in the Databases section of cPanel Home.




Create a New Database

When MySQL Databases interface will open, first thing you will see is Create New Database Section as shown below.



To create a database, simply enter the name of the database you wish to create and then click Create Database Button. You will now get a success message that the database is added.




Note: cPanel will automatically add a prefix to your database name you enter. So that there is no ambiguity in databases as in shared hosting environment. There are many users and there cannot be same name for two databases, thus your database name become *Prefix_dbName*. When connecting the database with web application you will need to use Full Name of database.

Add a Database User

To use your newly created database in your application, you will need to create a user and grant it all the privileges to modify the data in Database.

To create a Database User, scroll down to the end in Interface of MySQL databases. There you will see MySQL users, under it there will be Add New User, as shown below.




MySQL Users

Add New User

Username
tutorial_ NewUser

Password
.....

Password (Again)
.....

Strength  Password Generator


Create User

Step (1) – Enter a username according to your choice and choose a strong password. Click Create User to create a new user. You will get a success message “You have successfully created a MySQL user.”

Note: Full username of your database user includes prefix and the username you provided.

As we have created a database user, now we will need to add the user to access the database.

Step (2) – Scroll down to find “Add User to Database”.



Add User To Database

User
tutorial_NewUser

Database
tutorial_NewDB

Add

Step (3) – Select the User and database you wish to associate together. Click Add button and you will see the following screen.

MySQL® Databases

Manage User Privileges

User: **tutorial_NewUser**
Database: **tutorial_NewDB**

ALL PRIVILEGES

ALTER ALTER ROUTINE

CREATE CREATE ROUTINE

CREATE TEMPORARY TABLES CREATE VIEW

DELETE DROP

EVENT EXECUTE

INDEX INSERT

LOCK TABLES REFERENCES

SELECT SHOW VIEW

TRIGGER UPDATE

[Make Changes](#)

[Go Back](#)

To provide all the privileges to the user, select ALL PRIVILEGES checkbox and all the checkboxes will automatically get selected. Click **Make Changes** to save the changes.

Modifying a Database

The data stored in MySQL may get corrupted over time. There are many reasons for which this might happen. While using the Database in web application, if we see any database related error, we need to repair the database to repair the corrupt data. But before we repair our database, we will need to find the table on which our data is corrupted by checking the database for errors.

There are two operations we can perform to troubleshoot database related errors. To perform these actions, we need to scroll to Modify Database Options in MySQL Database Interface, screenshot for Modifying Database is shown below.

Modify Databases

Check Database

▼

Repair Database

▼

Check a Database

With this feature of cPanel Database, you can find which table in the Database is corrupted.

To check a database, we need to perform the following steps.

Step (1) – Select the database you want to check, from the dropdown menu of Check Database, as shown above.

Step (2) – Click the Check Database button.

Step (3) – cPanel will now run an automated script to find the corrupt table in the Database. If any corrupt table is found, it will display the name of the Table, otherwise it will display a success message.

Repair a Database

This database tool helps in automatically repairing of corrupt data or table from the database.

To use this tool, we need to perform the following steps:

Repair Database

▼

Step (1) – Select the database having corrupt data from the dropdown menu.


Step (2) – Click Repair Database button.

Step (3) – cPanel will now run an automatic script to repair the corrupt data or table from the database, if it succeeds, it will give you a success message. If it fails to repair the database, it will show you an error with the table name on which the error occurred.


24. cPanel – MySQL Database Wizard

MySQL Database Wizard is a step by step process to create a MySQL database and user and finally adding the user to access the database.

To use this interface, we will need to open MySQL Database Wizard, which can be found in the database section of cPanel Home, as shown below.



Step (1) – Create a New Database by providing a Database Name in the text input, once filled, click **Next Step**.



Step (2) – Create Database user by providing a username and Password. Click **Create User** when done.

The screenshot shows the MySQL Database Wizard interface. At the top, it says "MySQL® Database Wizard". Below that, a green notification bar states "Added the database 'tutorial_NewDB2'". The main heading is "Step 2: Create Database Users:". Under "Username:", there is a text input field containing "tutorial_ NewUsr" and a note "Note: 7 characters max.". Under "Password:", there is a password input field with masked characters. Under "Password (Again):", there is another password input field with masked characters. A "Strength" indicator shows a green bar labeled "Very Strong (100/100)". To the right of the strength bar is a "Password Generator" button. At the bottom left is a blue "Create User" button.

Step (3) – Add user to the database by granting all the privileges to the user for accessing and modifying the data. Select ALL PRIVILEGES checkbox and click Next Step, when done.

The screenshot shows the MySQL Database Wizard interface for Step 3: "Add user to the database.". At the top, a green notification bar states "You have successfully created a MySQL user named 'tutorial_NewUsr'.". Below the heading, it shows "User: tutorial_NewUsr" and "Database: tutorial_NewDB2". A list of checkboxes is shown, all of which are checked. The first checkbox is "ALL PRIVILEGES". Below it, there are two columns of checkboxes: ALTER, CREATE, CREATE TEMPORARY TABLES, DELETE, EVENT, INDEX, LOCK TABLES, SELECT, and TRIGGER in the left column; and ALTER ROUTINE, CREATE ROUTINE, CREATE VIEW, DROP, EXECUTE, INSERT, REFERENCES, SHOW VIEW, and UPDATE in the right column. At the bottom left is a blue "Next Step" button.


Step (4) – You will get a success message if everything works fine.

To modify the database created using MySQL Database Wizard, you can always use MySQL Databases interface.


25. cPanel – phpMyAdmin

The phpMyAdmin is a third-party tool to manage tables and data inside a database. It is graphical user interface to manage MySQL databases. You can manually create Tables, Import and Export data or edit the values of a row through it.

To access phpMyAdmin, click on the phpMyAdmin link, which can be found under the databases section of cPanel Home.



You will see a dashboard similar to this.



On the left hand pane, there is a list of databases, which can be expanded to see the table in each database. On the right hand pane, there is general information of Database server.

Execute an SQL Query

To execute an SQL Query on a database, we will need to perform the following steps:

Step (1) – Select the database from left pane by clicking over the name of the database. Once the database is selected, it will show you the structure of the database.

Step (2) – Click on SQL from top bar to open SQL editor.




Table	Action	Rows	Type	Collation	Size	Overhead
<input type="checkbox"/> test	Browse Structure Search Insert Empty Drop	0	MyISAM	latin1_swedish_ci	1 KiB	-
1 table	Sum	0	MyISAM	latin1_swedish_ci	1 KiB	0 B

↑ Check All With selected: ▾

Step (3) – Write your query into the SQL editor. You can also enter multiple queries, separated by semicolon (;).



Run SQL query/queries on database tutorial_NewDB: [+](#)

```
1 INSERT INTO test VALUES(1,2);
```

Clear


[Delimiter ;] Show this query here again Retain query box Go

Step (4) – Click **Go** button to execute the query. If the query is executed successfully, you will get a success message.

26. cPanel – Remote MySQL


This feature of cPanel allows remote servers or web application to access a database hosted on your account. If a server or web application tries to access the database on your account, which is not provided access to, then cPanel will not allow this host to access your database. But, if you have an application, whom you wish to grant access to your databases, you can add their host names or IP address here.

To access this interface, click on Remote MySQL link found in your Database Section of your cPanel.



Add Access Host

To Add Access Host, which can access your databases when needed. You will have to enter Host Name in text input. You can enter hostnames in three types.




- You can use Domain Name, E.g. www.tutorialspoint.com
- You can use IP address, E.g. 184.168.144.133
- You can use wildcard %, E.g. %.tutorialspoint.com or 184.164.144.%

Click on Add Host to add an access host.

Remove Access Host

To deny access to a web application having access to the databases, click the Delete link from the list of Access host.

Access Hosts	Remove
184.164.133.144	 Delete


27. cPanel – Subdomains

Subdomain is a domain, which is a part of a primary domain and exists in the same server. We can also say it is a second website, which resides under the main domain, however it may or may not have any relation with the root website. we can run a new website under this subdomain.


For Example – The **blog.tutorialspoint.com** is a subdomain for the root domain **tutorialspoint.com** and blog.tutorialpoint.com can also be accessed by tutorialpoint.com/blog.

To Create a Subdomain

Step (1) – Click Subdomains, which can be found under Domains section.



Step (2) – Enter the Subdomain text you want to create. Select the root Domain for your subdomain and the Document Root will be automatically filled according to your Subdomain. You may leave it as it is or you may change it according to your need. Click Create button to create your Subdomain.



If your subdomain is created successfully, then you will see a Success message like the one shown below.



Subdomains

Success: "test.tutorialspoint.com" has been created.

Managing Redirection

If you want your subdomain to point to another domain rather than loading content from your own server, you can do so by clicking Manage Redirection as shown below.




Modify a Subdomain

Search

Subdomains.Root Domain	Document Root	Redirection	Actions
test.tutorialspoint.com	/public_html/test	not redirected	<input type="button" value="Remove"/> <input type="button" value="Manage Redirection"/>

Page: Per Page:

You will be taken to the screen, where you can manage redirection for your subdomain. Enter the new URL, where you want to redirect your subdomain to. Click save and your redirection will be saved successfully. If you want to disable the redirection later on, you may click Disable Redirection.



Subdomains

Redirection

"test.tutorialspoint.com" redirects to:

28. cPanel – Aliases


This feature of cPanel allows your website to load from another domain. When a user enters the Alias Domain or Parked Domain to access the website, the cPanel automatically redirects them to your main domain and load the main website.

For Example, consider your main domain is www.mymaindomain.com and you have also bought www.myanotherdomain.com and www.mymaindomain.in, and you want to display your same website to these other domains, you have also bought. There is no need to purchase separate hosting for these domains and copy the website to these domains. You can use cPanel Aliases to point these domains to your main domain.


Create an Alias

To create an alias, you will need to follow these steps:

Step (1) – Open cPanel Aliases by clicking on the Aliases link found in Domains Section of cPanel Home.



Step (2) – In the Aliases section, you will see Create New Alias, fill your domain in the text box.



Step (3) – Press Add Domain button to add an alias, if successful you will see a success message.

Note: 1. Domain must be registered already. 2. Domain's Nameservers must be configure to point at your cPanel account.

Remove Aliases

To remove alias created before, you need to follow these steps:

Step (1) – Navigate to Remove Aliases Section, which can be found under Remove Aliases.


Remove Aliases

Aliases are relative to your account's home directory. The home icon (🏠) signifies your home directory which is "/home/liptanxy".

Domain	Domain Root	Redirects To	Actions
abc.com	🏠 /public_html	not redirected	<input type="button" value="Remove"/> <input type="button" value="Manage Redirection"/>
myexample.in	🏠 /public_html	not redirected	<input type="button" value="Remove"/> <input type="button" value="Manage Redirection"/>

Page:
 Per Page:

Step (2) – Click on the Remove link from Actions corresponding to the Domain you want to remove and you will see the following remove prompt.



Aliases


Are you sure you want to permanently remove the alias, "abc.com"?

Step (3) – Click on Remove Alias Button, if successful you will see a success message.

29. cPanel – Addon Domain

Addon Domains are additional domains hosted in your account, stored in subfolders. System treats these domains as a subdomain to your system. If you want to run a whole different website under the same hosting plan, you can use this feature of cPanel. It is the best option to run multiple websites on a single cPanel account. For example, you have a hosting for blogging website, and you want a different website for your CV, you will not need to purchase a different hosting account, but you can use the same hosting for your CV website.

To use this feature, you will need to click **Addon Domains** link under your Domains section from cPanel Home.




In Addon Domains interface, you can do the following tasks.

Create an Addon Domain

To create an Addon Domain, follow these steps:

Step (1) – Find Create an Addon Domain section in Addon Domains, as shown below.



Addon Domains

An addon domain is an additional domain that is stored as a subdomain of your main site. Use addon domains to host additional domains on your account without registering a new domain name. For more information, read the [documentation](#).

Create an Addon Domain

New Domain Name

Subdomain

Document Root 🏠

Create an FTP account associated with this Addon Domain.

Add Domain

Step (2) – Fill your domain name in New Domain Name textbox.

Step (3) – Subdomains and Document Root will be automatically filled. Then you can leave the setting as it is or you can change them according to your need.

Step (4) – You can create an FTP account, which will be associated with the Addon Domain. To create an FTP account, select the checkbox on which Create an FTP account associated with this domain is written.

Create an FTP account associated with this Addon Domain.

FTP Username

Password


Password (Again)

Strength ⓘ

Very Strong (100/100)

Step (5) – Enter FTP Username and Password to create an FTP account.

Step (6) – Click on the button “Add Domain”, if no error occurs, you will get a success message.

 **Addon Domains**





✓ The addon domain "myexample.in" has been created.
The FTP account "myexample" has been created.

Remove an Addon Domain

To remove an Addon Domain, Scroll down to “Modify Addon Domain” Section and press remove link from Actions corresponding to the Addon Domain.

Modify Addon Domain

Search

Addon Domains	Document Root	Subdomain	Redirects to	Actions
myexample.in	 /public_html/myexample.in 	myexample	not redirected	 Remove  Manage Redirection

Page: Per Page:

30. cPanel – Redirect

The redirect interface allows you to send all the visitors or traffic of a Domain or a particular webpage to a new domain. For example, if you moved your website to a new domain and you want to redirect all your visitors to new website, you need to setup redirect. There are two types of redirects available:

Permanent (301) Redirect

This one redirects your visitors to a new website and updates your visitor's bookmarks. This also directs search engines to your new website. This redirect is permanent and means that page has moved. So, the Search Engine and other crawlers update their data according to the new link. Popularity and SEO of link remains same as the old link had.


Temporary (302) Redirect

This one redirects your visitors to a new website, but does not update your visitor's bookmark. Search Engines still index your original website. This redirect is temporary and search engine thinks that the new link is going to get removed, hence it does not have same popularity like the old link.


Create a Redirect

To create a redirect, please follow these steps:

Step (1) – Click on Redirects found in Domains section of cPanel Home.



Step (2) – Choose your redirect type from the Dropdown Menu, Permanent or Temporary Redirect.



Redirections

A redirect allows you to make one domain redirect to another domain, either for a website or a specific web page. For example, create a redirect so that **www.example.com** automatically redirects users to **www.example.net**. For more information, read the [documentation](#).

Add Redirect

A permanent redirect will notify the visitor's browser to update any bookmarks that are linked to the page that is being redirected. Temporary redirects will not update the visitor's bookmarks.

Type

Permanent (301) ▼

http://(www)?

** All Public Domains ** ▼

Path

/

Redirects to

www. redirection:

Only redirect with www.

Redirect with or without www.

Do Not Redirect www.

Wild Card Redirect

Add

Step (3) – Choose the Domain Name you want to redirect from the Dropdown menu of lists of domain.

Step (4) – In the next textbox, enter the path of page or path of folder you want to redirect.

Step (5) – Enter full URL of the page your domain will be redirected to, in Redirect to textbox. You will also need to specify the protocol as well, http:// or https://.

Step (6) – Select www. redirection, it determines that if you want your domain to be redirected with www or not. Explanations of options given below.

- **Only redirect with www.:** This redirect will be done only if user has entered www. in URL.
- **Redirect with or without www.:** This redirect will always be done, does not depends on whether user has entered www. in URL or not.
- **Do not redirect www.:** This redirect will not work, if the user has entered www. in URL.

Choose your option accordingly, recommended is that you use **Redirect with or without www.**

Step (7) – Select Wild Card Redirection checkbox, if you want to redirect all files and folders in sub folder to the same file or folder in new domain. For example, with wildcard redirection **www.example.com/pic.jpg** will redirect to

www.new-example.com/pic.jpg. Without wildcard redirection
www.example.com/pic.jpg will redirect to Select the checkbox accordingly.

Step (8) – Click on **Add** button to save the settings.

31. cPanel – Simple Zone Editor


DNS (Domain Name System) is a very essential part of Internet System. It simply maps a FQDN (Full Qualified Domain Name), which is in human readable form. For example, `www.tutorialspoint.com` to IP address, which are used by computer machine, e.g. `117.18.237.191`. For this process, DNS uses zone files that are stored in servers, which contains resource records to map a domain name to an IP address.

In this Simple Zone Editor, we can add two types of records:

Add an A Record


The **A** types of resource records are Host Name records. They contain the IP address of a specific host, and maps the Domain Name with 32-bit IP address.

To add an A type record, perform the following steps:



Step (1) – Open the Editor by clicking **Simple Zone Editor** found in Domains Section of cPanel Home.

Step (2) – Find **Add an A Record** in the Simple Zone Editor interface.

A screenshot of the 'Simple Zone Editor' interface. At the top, it says 'Simple Zone Editor' with a 'DNS' icon. Below that, there is a brief description of DNS. The main section is titled 'Add an A Record' and contains two text input fields: 'Name' with the value 'example.com.tutorialspoint.com' and 'Address' with the value '184.164.133.144'. At the bottom of this section is a blue button labeled 'Add an A Record'.

Step (3) – Enter Name in Name textbox and IP address in Address textbox.

Step (4) – Press **Add an A Record**. If successful, you will get a success message.

Note: 'A' records are essential for accessing your website. They allow DNS servers to locate your website and its services. Without an 'A' record, visitors can't access your website. The cPanel automatically configures A type records for your domain and website, as soon as they are created.

Add a CNAME Record

The CNAME records are used to add an Alias to its associated domain name. You can point multiple CNAME records to a single A record. So that when the DNS looks up for the Alias, you can simply rename a host, which is defined in the A records.

To add a CNAME record, please follow these steps.

Step (1) – Scroll down on Simple Zone Editor to find **Add a CNAME Record**.

Add a CNAME Record

Name

CNAME

[Add CNAME Record](#)

Step (2) – Enter the desired Alias name for CNAME record on Name textbox and Enter a FQDN in CNAME textbox to which you want your Alias pointing to.

Step (3) – Click **Add CNAME Record** and you should see a success message.

Remove an A or CNAME Record

To remove a user defined **A or CNAME Record**, please scroll below on Simple Zone Editor to find **User-Defined Records**. Press the Delete link corresponding to the Record you want to remove.

User-Defined Records			
Name	Type	Record	Action
cpanel.tutorialspoint.com.	A	184.164.144.133	Delete
webdisk.tutorialspoint.com.	A	184.164.144.133	Delete
cpcalendars.tutorialspoint.com.	A	184.164.144.133	Delete
cpcontacts.tutorialspoint.com.	A	184.164.144.133	Delete

You should see a success message when record is deleted.

32. cPanel – Advance Zone Editor

This interface is the advanced version of Simple Zone Editor, which we have gone through in the previous chapter. We can add, edit or delete various types of records here, which are **A**, **AAAA**, **CNAME** (Conical Name Record), **SRV** (Service Record), **TXT** (Text Record). We can also configure **TTL** (Time to Live) with records in this interface.


TTL (Time to Live) indicates the time duration that DNS servers can cache resource records prior to discarding the information.

Reset Zone Files


This option resets every change that you made in your cPanel account regarding DNS records. It also resets the changes made using Simple Zone Editor.

To reset Zone Files, follow these steps:

Step (1) – Navigate to cPanel Advanced Zone Editor by clicking on **Advanced Zone Editor** link found in Domains Section of cPanel Interface.



Step (2) – Find Reset Zone File and click on **more** link.



Step (3) – It will show you a warning that all modifications in Zone files will be erased. Select the checkbox for the *Are you sure you want to erase all entries and revert to the default state?*

Reset Zone File

Reset the entries in your zone file to a default state. [less »](#)

Warning: Resetting your zone file will erase any modifications you have made to your zone records either below or in the Simple DNS Editor section. It will attempt to save TXT entries. Before resetting be sure to write down any changes you may want to save.

Are you sure you want to erase all entries and revert to the default state?

[Reset Zone File](#)

Step (4) – Press Reset Zone File button to reset the zone file to their default state. If successful, you will see a success message shown below.

✔ Zone File Reset Click to close. [X]

Add an A record

The 'A' type of resource records are Host Name records. They contain the IP address of a specific host and map the Domain Name with 32-bit IP address.

To add an A record, follow these steps.

Step (1) – Find **Add a Record** Section in the Advance Zone Editor.

Step (2) – Select Record 'Type A' from Type Dropdown Menu.

Add a Record

Type

A ▼

Name

TTL

Address:

[Add Record](#)

Step (3) – Enter Name of your **A** record. Enter TTL value, if there is no specific need, you can use default which is 14400. Also enter IP address of record in the Address textbox.

Step (4) – Click **Add Record** to save the record in the DNS entries.

Add an AAAA Record

The AAAA resource records bind hostnames with IPv6 Address, which is a 128-bit IP address.

Step (1) – Find **Add a Record** Section in the Advance Zone Editor.

Step (2) – Select Record type **AAAA** from the dropdown menu.

Add a Record

Type

AAAA

Name

justfortest.tutorialspoint.com.

TTL

14400

IPv6 Address

2001:0db8:0000:0000:0000:ff00:0042:8329

Add Record

Step (3) – Enter the Hostname in the Name textbox and TTL value in the TTL textbox, unless required use default TTL value, which is 14400.

Step (4) – Enter 128-bit IPv6 address in IPv6 Address textbox to which you want your hostname to bind.

Step (5) – Click **Add Record** to save this AAAA record in your DNS entries.

Add a CNAME Record

CNAME records are used to add an Alias to its associated domain name. You can point multiple CNAME records to a single **A** record so that when the DNS looks up for the Alias, you can simply rename a host, which is defined in **A** records.

To add a CNAME record, please follow these steps.

Step (1) – Find **Add a Record** Section in the Advance Zone Editor.

Step (2) – Select Record type **CNAME** from dropdown menu.

Add a Record

Type
CNAME

Name
justfortest.tutorialspoint.com.

TTL
14400

CNAME:
tutorialpoint.com

Add Record

Step (3) – Enter your Subdomain or Alias to Name text input, also provide TTL value in TTL textbox, unless required use default TTL value, which is 14400.

Step (4) – Enter a valid zone name or domain name to which you want this Alias to point to, in the CNAME textbox.

Step (5) – Press Add Record Button to save this CNAME record to your DNS entries.

Add an SRV Record

This resource record provides information about available services in the specific ports of your server. They associate the location of a service with details on how the service can be contacted on a specific domain. An SRV record must point to a hostname with an **A** record.

To add an SRV record, please follow these steps.

Step (1) – Find Add a Record Section in the Advance Zone Editor.

Step (2) – Select Record type SRV from dropdown menu.

Add a Record

Type
SRV

Name
_http_tcp.tutorialspoint.com.

TTL
14400

Priority
0

Weight
0

Port
80

Target
www.tutorialspoint.com

Add Record

Step (3) – Enter Name of Service and Protocol both preceded by an underscore (_) and separated by dot (.).

Step (4) – Provide TTL value in TTL textbox, unless required use default TTL value, which is 14400.

Step (5) – Provide Priority of the Service, the lower the number in priority, higher is the priority of the service. 0 (zero) has the highest priority.

Step (6) – Enter Weight of the service, it is used by zone administrators to distribute the load to multiple targets. 0 is the lowest load.

Step (7) – Enter the Port on which service is actually offered.

Step (8) – Enter Target, it is the name of the host that will receive this service.

Step (9) – Press Add Record to add this SRV record into your DNS entries.


Add a TXT Record

The TXT records can hold any type of text. A domain name can have many TXT records, most common TXT records are used to define SPF (Sender Policy Framework) or DKIM, which is used for Email Authentication.

To add a TXT record, please follow these steps.

Step (1) – Find Add a Record Section in the Advance Zone Editor.

Step (2) – Select Record type TXT from the dropdown menu.



Add a Record

Type

TXT

Name

tutorialspoint.com.

TTL

14400

TXT Data

v=spf1 +a +mx +ip4:184.164.144.130 ~all

Add Record

Step (3) – Enter Valid DNS Zone name in Name textbox.

Step (4) – Provide TTL value in TTL textbox, unless required use default TTL value, which is 14400.

Step (5) – Enter TXT Data, it can be any type of text, or a SPF or DKIM data.

Step (6) – Press Add Record Button to add this TXT record to DNS records.

Edit or Delete a DNS Record

To edit or Delete a DNS record, you added earlier. Follow these steps:

Step (1) – Scroll down to **Zone File Records** in Advanced Zone Editor.

Zone File Records					
Name	TTL	Class	Type	Record	Action
tutorialspoint.com.	14400	IN	A	184.164.144.133	Edit Delete
mail.tutorialspoint.com.	14400	IN	CNAME	tutorialspoint.com	Edit Delete
www.tutorialspoint.com.	14400	IN	CNAME	tutorialspoint.com	Edit Delete
ftp.tutorialspoint.com.	14400	IN	A	184.164.144.133	Edit Delete
tutorialspoint.com.	14400	IN	TXT	v=spf1 +a +mx +ip4:184.164.144.130 ~all	Edit Delete

Step (2) – Find the DNS resource record you wish to edit or delete from the list of records.

Step (3) – To Edit an entry, click **Edit** Link from Action, which is corresponding to the record you wish to edit.

tutorialspoint.com. 14400 IN TXT v=spf1 +a +mx +ip4:184.164.144.130 ~all [Edit](#) [Delete](#)

Name

TTL

Type

TXT Data

[Edit Record](#) [cancel](#)

Step (4) – Edit your record according to your need and Click **Edit Record** button to save the changes.

Step (5) – To delete a record click on **Delete** link corresponding to the record you wish to delete.

tutorialspoint.com. 14400 IN TXT v=spf1 +a +mx +ip4:184.164.144.130 ~all [Edit](#) [Delete](#)

Are you certain that you want to delete this record?

[Delete](#) [Cancel](#)

Step (6) – You will be asked for confirmation, press **Delete** button to delete the record.


33. cPanel – Email Accounts

You can create and manage email accounts of your domain through this interface. You can Create email address, configure your mail client, change your passwords and access your webmail directly.


Create an Email Address

To create an email address for your domain, follow these steps:

Step (1) – Click on **Email Accounts** link found in your Emails section of the cPanel Home.



Step (2) – In Email Accounts, you will find Add Email Account on the Top.

A screenshot of the 'Add Email Account' form in cPanel. The form includes fields for 'Email' (with 'info' entered), 'Domain' (with 'tutorialspoint.com' selected), 'Password', and 'Password (Again)'. A 'Strength' indicator shows 'Very Strong (100/100)' with a green bar. There is a 'Password Generator' button and a 'Mailbox Quota' section with '250 MB' selected and 'Unlimited' as an option. A 'Create Account' button is at the bottom.

Step (3) – Add Email name you want to create as it will be the text that comes before @.

Step (4) – Choose a strong password and supply Mailbox Quota. It defines how much disk space this account can use. You can provide specific amount of space in MB or you can provide an unlimited quota for this.

Step (5) – Click on Create Account to create an Email address associated with your domain.

Manage Email Accounts

You can manage your email accounts through this interface, you can change your passwords, change quota amount or delete the email account.

To manage your email accounts, scroll down to see the list of Email accounts that exist with your domain.

Change Passwords

To change your email accounts password, click *Change Password* link corresponding to your email address.

Enter New Passwords, and save changes by pressing Change Password button.

Change Quota

To change your email quota, click on link *Change Quota* corresponding to your email address that you want to manage.

Enter limited quota in Megabytes or select unlimited option. Press *Change Quota* Button so save the changes.

Configure Mail Client

To send and receive emails with your domain from any desktop or mobile email client, e.g. Windows Live Mail, Outlook or iOS of iPhone etc. cPanel provides you preconfigured setting for these applications. You just need to download the settings and run it, then it will automatically configure the email client. You may need to enter your email account password. You can also manually configure the email clients for sending and receiving emails for your email client.

To download *Auto Configuration Scripts* or See the manual settings, click on *Configure Mail Client* link corresponding to your email account.

Account @ Domain	Usage / Quota / %	Actions			
info@tutorialspoint.com	0 / ∞ MB	Change Password	Change Quota	Configure Mail Client	Delete More

Once the interface is opened, you will see *Auto Configuration Scripts*.

Application	Protocols
Windows Live Mail®	IMAP over SSL/TLS POP3 over SSL/TLS IMAP POP3 (Post Office Protocol v3)
Microsoft Outlook 2000® for Windows®	IMAP over SSL/TLS POP3 over SSL/TLS IMAP POP3 (Post Office Protocol v3)
Microsoft Outlook Express® for Windows®	IMAP over SSL/TLS POP3 over SSL/TLS IMAP POP3 (Post Office Protocol v3)
MacOS® Mail.app® for "Pre Lion" (10.4+)	IMAP over SSL/TLS IMAP
MacOS® Mail.app® for "Lion" (10.7+)	IMAP over SSL/TLS IMAP
iOS for iPhone/iPad/iPod and MacOS® Mail.app® for Mountain Lion (10.8+)	IMAP over SSL/TLS IMAP

You can download *Auto Configuration Scripts* for Configure mail client interface. Just download the appropriate settings and run it.

Or if you want to configure your mail client manually, you can scroll down to see the Manual Settings.

Manual Settings

If you do not see an auto-configuration script for your client in the list above, you can manually configure your mail client using the settings below:

<div style="background-color: #f0f0f0; padding: 5px; border: 1px solid #ccc;"> <p style="text-align: center; margin: 0;">Secure SSL/TLS Settings (Recommended)</p> <p>Username: info@tutorialspoint.com</p> <p>Password: Use the email account's password.</p> <p>Incoming Server: gains.supercloudapps.com</p> <ul style="list-style-type: none"> IMAP Port: 993 POP3 Port: 995 <p>Outgoing Server: gains.supercloudapps.com</p> <ul style="list-style-type: none"> SMTP Port: 465 <p style="font-size: small;">Authentication is required for IMAP, POP3, and SMTP.</p> </div>	<p style="text-align: center; margin: 0;">Non-SSL Settings (NOT Recommended)</p> <p>Username: info@tutorialspoint.com</p> <p>Password: Use the email account's password.</p> <p>Incoming Server: mail.tutorialspoint.com</p> <ul style="list-style-type: none"> IMAP Port: 143 POP3 Port: 110 <p>Outgoing Server: mail.tutorialspoint.com</p> <ul style="list-style-type: none"> SMTP Port: 25 <p style="font-size: small;">Authentication is required for IMAP, POP3, and SMTP.</p>
--	--

Note: There are four types of settings – IMAP and POP3, both over SSL/TLS and Non-SSL too. Using SSL sends your messages with encryption providing extra layer of security, but Non SSL does not. It is recommended that you use settings with SSL. From IMAP or POP3, you can choose anyone you want. Both will work perfectly.

Delete an Email Account

To delete an email account, just click on *Delete* link corresponding to your email account.

Account @ Domain	Usage / Quota / %	Actions
info@tutorialspoint.com	0 / ∞ MB	Change Password Change Quota Configure Mail Client Delete More ▾
Delete info@tutorialspoint.com?		
Delete Cancel		

It will ask for confirmation. Press the Delete Button to remove your email account.

34. cPanel – Email Forwarders

You can create multiple email account in your cPanel email as per your need. When the number of emails accounts get higher, you will need to open each account to view the emails received. To overcome this issue, you can forward the copy these emails of one account to another account, so now you will have to only open one account to view all the emails. You can also discard the email or send it to a program. You can also forward all the emails of your domains to another domain.

E.g. you have several email ids' like info@tutorialspoint.com, admin@tutorialspoint.com or support@tutorialspoint.com. Instead of opening 3 mailboxes to check emails, you can you can forward the last two to info@tutorialspoint.com. Now you will only have to access info@tutorialspoint.com to check your email.


Create an Email Forwarder

There are two types of forwarders available, first to forward an email account to another one. Second is to forward all emails to a domain.


Create an Email Account Forwarder

To create an email account forwarder please follow these steps:

Step (1) – Open Email Forwarders by clicking on the link of **Forwarders** found in cPanel Home.



Step (2) – In the Forwarders Interface, you will find *Create an Email Account Forwarder*.



Step (3) – Press Add Forwarder Button, it will take you to a similar interface like this.

Add a New Forwarder

Address

Address to Forward:

 @

Domain

 ▼

Destination

Forward to Email Address

Discard and send an error to the sender (at SMTP time).

Failure Message (seen by sender)

Add Forwarder

Step (4) – Enter the Address of the email which you want to forward. It is not necessary that the email must be already created. If you do not create an email and forward it to somewhere, the only difference will be that your emails will not be stored in the mailbox of the original email, because that mailbox will not exist.

Step (5) – Enter destination where you want your email to be forwarded.

- Select *Forward to Email Address* and fill the textbox with an existing email, where you want your emails to be received.
- Select *Discard and send an error to sender*. If you want to discard that message and supply a failure message to sender. You can also customize the Failure message, enter the message in textbox.

In Advance Options –

Advanced Options ▾

Forward to a system account

Pipe to a Program

When piping to a program, you should enter a path relative to your home directory. If the script requires an interpreter such as Perl or PHP, you should omit the /usr/bin/perl or /usr/bin/php portion. Make sure that your script is executable and has the appropriate target at the top of the script. If you do not know how to add the hashbang, just make sure to name your script file with the correct extension and you will be prompted to have the hashbang added automatically.

Discard (Not Recommended)

Add Forwarder

- Select *Forward to a System Account*, if you want your emails to be sent to a system account, and provide a system account name.


- Select *Pipe to a program*, if you want your emails to send to a program and enter path name of your program with file extension.
- Select *Discard* and system will simply discard the email and will do nothing. Select your choice accordingly.

Step (6) – Click *Add Forwarder* to save the changes you made.


Add Domain Forwarder

You can forward all the emails of your domain to another domain. On the domain, who will receive the emails, you can change the default email address of that domain to a single email, which then can receive all the emails sent from your domain of which you forwarded the emails.

Step (1) – Click on *Add Domain Forwarder* button, which can be found under *Create an Email Forwarder* of Forwarder interface.



Step (2) – In *Add New Domain* Interface, select the domain you want to forward.



Step (3) – In the textbox next to your domain, enter the domain on which you will be receiving the emails.

Step (4) – Press *Add Domain Forwarder* button to save the changes.

Delete an Email Forwarder

To delete an email forwarder, click on delete link corresponding to the forwarder you want to delete.

For Email account forwarder –

Email Account Forwarders

Send a copy of any incoming email from one address to another. For example, forward **joe@example.com** to **joseph@example.com** so that you only have one inbox to check. For more information, read the [documentation](#).

Email Address	Forward To	Actions
admin@tutorialspoint.com	info@tutorialspoint.com	Trace Delete

For Domain Forwarders –

Forward All Email for a Domain

In addition to forwarding individual mail accounts, you can forward all email from one domain to another.

Domain	Forward To	Delete
tutorialspoint.com	newdomain.com	Delete

It will ask for your permission before deleting the forwarders, click Delete Forwarder to delete the Email Forwarder.

35. cPanel – Webmail

Webmail is a web-based email client, which allows you to access your emails through any browser or any computer. This is very helpful when you do not have access to your computer on which your email is setup, you can login to your account from anywhere to read your emails and to quickly respond.


Opening Your Webmail

There are two options through which you can login to your webmail client.


Through cPanel Interface

Follow these steps to login to your webmail client:


Step (1) – Login to your cPanel and click on Email Accounts found under the Email section.




Step (2) – Scroll down to find list of Email Accounts.



Step (3) – Click on More button at the corresponding email address of which you want to access webmail.




Step (4) – Click on Access Webmail and the system will automatically log you into the webmail in a new tab.



Step (5) – Choose any Webmail application. You can also set a default Webmail application, so whenever you log into your webmail, your default webmail application will automatically load.

Note: I have chosen **horde** to load webmail.




Access webmail directly

To access webmail directly without logging into cPanel, you can use the following steps:

Step (1) – Navigate to <https://your-domain.com:2096> or <https://webmail.your-domain.com> through your browsers address bar.

Step (2) – Webmail login screen will appear, Enter your Email and Password of your email account.



Step (3) – Press Log in button to login into your web based email client, you will get same interface as we got above.

36. cPanel – MX Entry


This feature of cPanel allows to route all your emails to a specific server. Changes you make here also get reflected in the domain's DNS entries. This feature is important to create a backup server for your domain's mail server to receive when your main server is down. You can setup MX entries here to route your mail to Google mail servers when you use Google Apps to manage your emails.

Use this interface to manage your MX entries and Email Routing


Configure Email Routing

To configure the email routing for your domain, follow these steps:


Step (1) – Open cPanel MX Entries by clicking MX Entry from Email Section of cPanel Interface.



Step (2) – Select the domain for which you want to configure Email Routing.



Step (3) – When you will select the domain from the drop down, Email Routing setting will appear. The current applied setting is displayed bold.



Domain

tutorialspoint.com

Email Routing

Warning: Setting the wrong option here can break receiving mail on your server. If you are at all unsure about which option to select, contact your system administrator.

Automatically Detect Configuration (recommended) more »

Local Mail Exchanger more »

Backup Mail Exchanger more »

Remote Mail Exchanger more »

Change

Current setting is shown in bold.

Step (4) – Change your current setting only when you need it. Select any of these four options according to your need.

- **Automatically Detect Configuration:** This enables the cPanel to automatically detect the best settings according to priorities of your MX records.
- **Local Mail Exchanger:** This enables your server to receive emails, even if any MX entry of higher priority is found. In this case, emails are sent to both domains.
- **Backup Mail Exchanger:** In this case, your server acts as backup mail exchanger and if your primary mail exchanger is offline, then it holds the emails until your primary server is back online. You need to have a proper MX Entry for your primary mail exchanger.
- **Remote Mail Exchanger:** In this case, your domain does not accept any mail and reroutes them to your primary email server.

Step (5) – Click Change and your new setting will appear in bold letters.

Add an MX Record

To add a, MX record, follow these steps:

Step (1) – Scroll down to Add New Record on MX Entry page.

Add New Record

Priority:

Destination:

[Add New Record](#)

Step (2) – Enter Priority of MX record, lower the number – higher the priority. Zero has the highest Priority.

Step (3) – Enter Destination Domain to which you want to reroute your emails.

Step (4) – Click Add New Record to add a new MX record.

Edit or Remove an MX Record

To edit or remove click Edit or Remove link in Actions corresponding to the MX entry that you want to edit or delete.

MX Records

Priority	Destination	Actions
0	mail.tutorialspoint.com	Edit Remove

When you will click Edit, it will ask you for the Priority and Domain, change what you need to change and finally click Edit to save the changes.

MX Records

Priority	Destination	Actions
0	mail.tutorialspoint.com	Edit Remove

Priority

Destination

[Edit](#)
[Cancel](#)

When you click Remove link, it will ask you for confirmation. Click Delete to remove the entry.

MX Records

Priority	Destination	Actions
0	mail.tutorialspoint.com	Edit Remove

Are you sure you want to delete this record?

37. cPanel – Autoresponders


You can add or modify Autoresponders for your email accounts through this interface. You can configure an email to send an automated reply to all emails you receive to your email account. You can make an automated reply to say that you have received the email and you will reply soon.

If you are on vacation, you can configure the Autoresponders to reply that you are not available at this moment etc. you can also set a specific duration of time in which the automated reply will be sent.


Add an Autoresponder

To add an autoresponder, follow these steps:

Step (1) – Open cPanel Autoresponders by clicking on Autoresponder link found in Email section of cPanel Home.



Step (2) – Click Add Autoresponder in this section. It will take you to Modify/Add Autoresponders.



Step (3) – Choose character set, recommended is that you leave it as it is, which is **utf-8**.

Modify/Add Autoresponder

Hint: If you do not create a forwarder or email account with the same address as this autoresponder, mail will only be handled by the autoresponder before it is discarded.

When configuring an autoresponder, you can use the following tags to insert information into the response email:

%subject%
The subject of the message sent to the autoresponder.

%from%
The name of the sender of the message received by the autoresponder, if available.

%email%
The incoming email sender's address.

Character Set:

utf-8

Note: You must select this option before changing anything else or you will lose your changes.

Interval:

hours

The number of hours to wait between responses to the same email address.

Step (4) – Enter the number of hours to wait between responses to same email address, this helps in preventing sending same email to same user multiple times.

Step (5) – Enter Email and select Domain for which you want to add an autoresponder.

Step (6) – Enter outgoing email's sender name, it may be your name or your company's.

Email:

info @

Domain

tutorialspoint.com

From:

TutorialsPoint

Subject:

%subject%

Step (7) – Enter Subject of your outgoing Email. You may keep it same as incoming email by putting %subject% in Subject, you can provide your custom subject too.

Step (8) – Enter Body of your Email. You may use %from%, which will be the name of sender, if available. You may use %email% in body too, it will be the email address of the sender.

This message contains HTML.

Body:

Hi %form%,

Thank you for contacting us, we will respond to your query as soon as possible.

Regards

Step (9) – Select *This message contains HTML* checkbox, if there is HTML in your Email Body.

Step (10) – Schedule a Start, End Date, and Time for your autoresponder email. You can choose to start immediately or on a specific date at a specific time. You can choose this autoresponder to stop sending emails on a specific day, or you can choose never to stop an autoresponder. You can change this configuration anytime.

Start:

Immediately

Custom

Stop:

Never

Custom

[Create/Modify](#)

Step (11) – Press Create/Modify button to create an autoresponder.

Edit or Delete Autoresponder

To edit or delete an autoresponder, find the Current Autoresponder by scrolling down in Autoresponder section.

Current Autoresponders

If you do not create a forwarder or email account with the same address as each autoresponder, mail sent to the autoresponder will only be handled by the autoresponder before it is discarded.

Email	Subject	Actions
info@tutorialspoint.com	%subject%	Edit Delete


Click Edit corresponding to the autoresponder to edit and it will take you to the same interface, which we have gone through when creating the Autoresponder. You can use the same interface to make the change.

To delete an autoresponder, click Delete corresponding to that autoresponder. It will ask you for confirmation, click Delete to delete that autoresponder.


38. cPanel – Track Delivery

This Interface of cPanel is used to see delivery reports of emails. This interface can show the errors, while sending your email. You can also see spam scores of your emails. A spam score is provided by **Apache Spamassassin**. You can also check the emails delivery route to help you identify any problems in the delivery attempt.

To track an email delivery, open cPanel Track Delivery by clicking on Track Delivery link found in the Email Section of cPanel.



In track Delivery interface, you will see a table of email sending events.

A screenshot of the cPanel Track Delivery interface. It shows a search bar for 'Recipient Email (optional)', buttons for 'Show All' and 'Show Blocked & Failed', and a table of email sending events. The table has columns for Event, Sender, Sent Time, Spam Score, Recipient, Result, and Actions. The first two rows show failed deliveries with error messages, and the third row shows a successful delivery.

Event	Sender	Sent Time	Spam Score	Recipient	Result	Actions
!	info@tutorialspoint.com	Jan 25, 2016 10:58:10 AM	0	root@gains.supercloud apps.com>	retry timeout exceeded	i
!	info@tutorialspoint.com	Jan 25, 2016 10:58:10 AM	-3	hdjhdhfskjhfkjfk@mail.com	SMTP error from remote mail server after initial connection: 554-mail.com (mxgmxus005) Nemesis ESMTSP Service not available\n554-No SMTP service\n554-IP address is black listed\n554 For explanation visit http://postmaster.gmx.com/en/error-m	i
✓	info@tutorialspoint.com	Jan 25, 2016 10:49:10 AM	0	info@tutorialspoint.com	Accepted	i

If you wish to filter the table for a single recipient email, you may do so by entering a recipient's email in Recipient Email (optional), and then click Show All

button to show the email related to a specific recipient. To view all emails again, remove the email from Recipient Email and Click Show All, it will again show all the records.

There are four main types of filters, which you can apply to a list.



- **Show Success:** This will show all the emails that are successfully delivered to the destination.
- **Show Deferred:** This will show you all emails with a warning, which are the system deferred emails.
- **Show Failures:** It will show you the emails, which are not delivered to the destination. It will also show any other errors during transmission of emails.
- **Show In-Progress:** This will show you all the emails, which are currently transmitting.

You can combine these filters too as and how they are required.

The following table shows the default information about emails:

Event	This column shows icon of success, failure or deferred emails.
Sender	It shows the email address of email sender.
Sent time	It shows the date and time on which email was sent.
Spam Score	It shows Apache Spamassassin spam score.
Recipient	It shows the email of recipient.
Result	Important column – it shows the error encountered by the system, while sending the email. This message describes the delivery results
Action	An information Icon, which on clicking shows the details of the report.

To view more information of an email delivery report, click information icon shown at the action column next to the corresponding report.

	info@tutorialspoint.com	Jan 25, 2016 10:58:10 AM	-3	hdjhdhtfskjhtkjjf@mail.com	SMTP error from remote mail server after initial connection: 554-mail.com (mxgmxus005) Nemesis ESMTP Service not available\n554-No SMTP service\n554-IP address is black listed.\n554 For explanation visit http://postmaster.gmx.com/en/error-m	
---	-------------------------	--------------------------	----	----------------------------	---	---

And you will see the details of the delivery record as shown below.

Delivery Event Details Close

Event:	failure !
User:	tutorialspoint
Domain:	tutorialspoint.com
Sender:	info@tutorialspoint.com
Sent Time:	Jan 25, 2016 10:58:10 AM
Sender Host:	gains.supercloudapps.com
Sender IP:	::1
Authentication:	dovecot_plain
Spam Score:	-2.9
Recipient:	hdjhdhfskjfhkjjf@mail.com
Delivery User:	
Delivery Domain:	
Delivered To:	
Router:	dkim_lookuphost
Transport:	dkim_remote_smtp
Out Time:	Jan 25, 2016 10:58:10 AM
ID:	1aNZhC-000Aje-8d
Delivery Host:	mx00.mail.com
Delivery IP:	74.208.5.20
Size:	797 bytes
Result:	SMTP error from remote mail server after initial connection: 554-mail.com (mxgmxus005) Nemesis ESMTP Service not available\n554-No SMTP service\n554-IP address is black listed.\n554 For explanation visit http://postmaster.gmx.com/en/error-m

Print Close

39. cPanel – Email Filters

Email filters are useful to create rules to block unwanted emails, based on certain rules you choose. You can specify some rules like a message containing a specific word should be deleted or passed to a specific program. These filters work subsequently, for example if a mail passes through a filter, but can be blocked by another filter. You can specify multiple rules in one filter too.

There are two types of Email Filters in cPanel: User Level Filter and Account Level Filter.


User Level Filter

Through this user level filter, you can create email filters, which will apply on emails that will be received by that email address.


Create a User Level Filter

To create a user level email filter, follow these steps:


Step (1) – Open user level email filters by clicking on Email Filter found under Email section of cPanel.



Step (2) – In Email Filters, you will see the list of emails associated with your domain. Click on Manage Filter link corresponding to your email on which you want to create a filter.



Step (3) – Click on Create New Filter button to go to a new filter creation interface.



Step (4) – Provide a name for your filter.

Step (5) – Select rules for filtering your message. To add additional rules, click on Add (+) button on right side, to remove rules click Subtract (-). Also choose 'and' or 'or' rule.

Step (6) – Select an Action for a message those passes to the rules of filter. To add additional rules, click on Add (+) button on right side, to remove rules click Subtract (-).

Step (7) – Click on Create button to create a filter.

Edit or Delete a User Level Filter

To edit or delete a user level filter:

Step (1) – Return to Email Filter Interface.

Step (2) – Choose the email for which you want to edit or delete the Filter from Current Filters.



Step (3) –

- To Edit, click Edit Link and you will be taken to the same interface we went through to create an Email Filter. Click Save to Save the Email Filter.
- To Delete the Email Filter, click on Delete link and you will be asked for confirmation. Click Delete to delete an Email Filter.

Testing an Email Filter

To test the filter, you can follow these steps:

Step (1) – Return to Email Filters Interface and Click on the Manage link corresponding to email address of which you want to test filter.

Step (2) – Scroll down to find Filter Test.


Step (3) – Enter complete Email with headers and subjects in Filter Email text input.

Step (4) – Press Test Filter and the system will generate a full report of how the filters will respond to the email you have written.

Account Level Filtering

The only difference in User Level Filtering and Account Level Filtering (or Global Email Filtering) is that the filters used in Account Level Filter will filter all emails received in your domain, no matter to which email address the message was sent.

To Create and Manage Global Email Filter click on Global Email Filter found under Email section of cPanel Home.



Process to Create, Manage and Test a Global Email Filter is same as we studied above in User Level Filtering. Only difference is that you will not find a list of Emails to choose to Manage, but you will get a list of all Global Email Filters.

40. cPanel – Authentications

Email Authentications prevent the email from going into the spam folder of recipients. cPanel uses DKIM and SPF to reduce the amount of spam mails. Enabling these features will prevent spammers from forging messages that claims to be coming from your domain.

DKIM


Domain Key Identification Mechanism (DKIM) verifies your incoming emails to check whether they are same as they were before when they were sent. This means, if they are altered during the transit. It also checks whether they are from the same address, whom they claim to be. This feature prevents incoming spam emails.

When DKIM is enabled, the sender signs the email with a digital signature using a private key. When the email approaches the recipient, it retrieves the public key of its sender and checks if the signature matches. If the signature is invalid, then message is treated as a spam message.


Enabling DKIM

To enable DKIM follow these steps:

Step (1) – Open Email Authentication by clicking Authentication found under Mail Section of cPanel Home.



Step (2) – Find DKIM settings, if disabled then, click **Enable** button to Enable DKIM.




Disable DKIM

To disable DKIM follow these steps:

Step (1) – Open Email Authentication by clicking Authentication found under Mail Section of cPanel Home.

Step (2) – Find DKIM setting, if enabled, then click **Disable** button to Disable DKIM.



Note: To Enable DKIM, your Nameservers must point to your hosting. It is recommended that you use DKIM Authentication in your hosting.

SPF


Sender Policy Framework (SPF) helps in preventing outgoing messages to spams. This helps to prevent spammers in creating a message that looks like it is originated through your domain. SPF uses TXT type DNS resource records, which specify the hosts that send emails through your domain.

Enable SPF

To enable SPF, follow these steps:

Step (1) – Open Email Authentication by clicking Authentication found under Mail Section of cPanel Home.

Step (2) – Find SPF setting, if disabled, then click **Enable** button to Enable SPF.



Disable SPF

To disable SPF, follow these steps:

Step (1) – Open Email Authentication by clicking **Authentication** found under Mail Section of cPanel Home.

Step (2) – Find SPF setting, if enabled, then click **Disable** button to disable SPF.

SPF

The SPF system allows you to specify servers and IP addresses that are authorized to send mail from your domain(s). This feature works to prevent outgoing spam messages.

Status: Enabled (DNS Check Passed) Active (DNS Check Passed)

[Disable](#)


41. cPanel – Address Importer

cPanel address importer can be used to create multiple email address or forwarders in your account. For example, you have 100 employees in your office and you want each employee to have an email address, then if you have a list of email addresses of employees, then within two clicks, you can create as many email accounts as needed. cPanel address importer supports two type of data import, **Excel Spreadsheet** (.xls) or **Comma separated value sheet** (.csv). You can also use this interface import email forwarder list.


Importing Email Addresses

To import email address, follow these steps:

Step (1) – Open cPanel Address Importer by clicking on Address Importer link found in the Email Section.



Step (2) – Select the Email address option in **What would you like to import.**



Step (3) – Browse and select your Excel Spreadsheet or CSV file. If you have selected XLS file, then it will only ask to treat the first row as column header, if yes, then select the check box. If you have selected CSV file, then it will ask for the delimiter. In most cases, it is a Comma, choose the one you have, and Click Next.

Note: You can see an example screenshot below. You can create a spreadsheet using Microsoft Excel, and save the spreadsheet using .xls or .csv in Save As menu.

	A	B	C	D
1	Email or Name	Password	Quota	
2	hello@tutorialspoint.com	XEsjhjh1242	300	
3	Liptan Biswas			
4	test@tutorialspoint.com			
5				

Step (4) – In the next step, it will ask you to choose a header for each column, choose an appropriate one. Select the domain in which you want to create the emails. Click Next.

Import E-mail Accounts

Step 1

Choose the header from the dropdown in the table that corresponds to each column.

<input type="text" value="Email"/>	<input type="text" value="Password"/>	<input type="text" value="Quota (MB)"/>
hello@tutorialspoint.com	XEsjhjh1242	300
Liptan Biswas		
test@tutorialspoint.com		

Step 2

Select the domain for the users in the list. **NOTE:** You will see an appended list if the column contains a list of usernames instead of email addresses.

Domain

Step (5) – In the final step, it will show you a review of what is going to be created. Review the Table, take a screenshot or print the page, so that you will have a copy of passwords corresponding to the emails.

Import E-mail Accounts

Review the following email accounts.

E-mail Address	Password	Quota (MB)
hello@tutorialspoint.com	XEsjhjh1242	300
lipanbiswas@tutorialspoint.com	4U(IN>3y&M&	unlimited
test@tutorialspoint.com	n)zA?Hj)=-@f	unlimited

[Finish](#)


Note: As you can see above for email column, which we did not provide an appropriate email, cPanel has automatically generated an Email for that name. In the password column, which we did not provide a password, cPanel has automatically generated them. While, in the Quota column, where we did not mention the Quota, cPanel has automatically provided unlimited quota.

Step (6) – Click finish to Import the Email addresses.

Importing Email Forwarders


To import Email forwarders, please follow these steps:

Step (1) – Open cPanel Address Importer by clicking Address Importer link found in the Email Section.



Step (2) – Select **Forwarders** option in *What would you like to import*.

This feature allows you to use 2 types of files to create multiple email address or email forwarders for your account simultaneously. You may use Excel spreadsheet files (.xls) or a comma-separated values sheet, aka CSV file (.csv) to import the data. A CSV file is a plain text file that has been given a .csv extension.

 Need help setting up a CSV or Excel file for importing? Check out our [example page](#).

Step 1: Select what you would like to import.

E-mail Accounts

Forwarders

Step 2: Locate CSV or XLS file on your computer.

Book1.xls

Step 3

Treat first row as column headers.

Step (3) – Browse and select your Excel Spreadsheet or CSV file. If you have selected XLS file, then it will only ask to treat the first row as the column header, if yes, then select the check box. If you have selected the CSV file, then it will ask for a delimiter. In most cases, it is Comma, choose the one you have, and then Click Next.

Note: You can see an example screenshot below. You can create a spreadsheet using Microsoft Excel, and save the spreadsheet using .xls or .csv in Save As menu.

	A	B
1	Forward from	Forward to
2	hello@tutorialspoint.com	info@tutorialspoint.com
3	test2@tutorialspoint.com	info@tutorialspoint.com
4	test@tutorialspoint.com	info@tutorialspoint.com
5		

Step (4) – In the next step, it will ask you to choose a header for each column. Select your source and destination column and click **Next**.

Import Forwarders

Choose the header from the dropdown in the table that corresponds to each column.

Source	Target
hello@tutorialspoint.com	info@tutorialspoint.com
test2@tutorialspoint.com	info@tutorialspoint.com
test@tutorialspoint.com	info@tutorialspoint.com

Step (5) – In the final step, it will show you a review of which forwarders are going to be imported. Review the settings.

Import Forwarders

Review the following forwarders.

Source	Destination
hello@tutorialspoint.com	info@tutorialspoint.com
test2@tutorialspoint.com	info@tutorialspoint.com
test@tutorialspoint.com	info@tutorialspoint.com

[Finish](#)

Step (6) – Click finish to Import the Forwarders.

42. cPanel – Encryption


cPanel supports GnuPG or GNU Privacy Guard, which is an open-source software to encrypt and decrypt messages using cryptographic algorithms. GnuPG uses a public and private key infrastructure to implement this feature.

When the sender sends a message, he encodes it with a public key of the recipient. The recipient after receiving the message, decrypts the message with his private key, which is available in the server. This feature helps in sending emails with sensitive information, as without a private key, it's nearly impossible to decode the message.


Create a GnuPG Key

To create a GnuPG key, follow these steps

Step (1) – Open cPanel Email Encryption by clicking on Encryption in the Email section of the cPanel Link.



Step (2) – In create a New Key interface, Enter Your name and Email.



Encryption

GnuPG is a publicly available encryption scheme that uses the "public key" approach. With GnuPG, messages are encrypted using a "public key" however, they can only be decrypted by a "private key", which is retained by the intended recipient of the message.

Create a New Key


Your Name

Your Email

Comment or Nickname:

Key Password

Confirm Password:

Strength  Very Weak (0/100) Password Generator

Expiration Date:

Format: 1y (1 year) 3w (3 weeks) 5d (5 days) 0 (No expiration date)

Key Size:

Step (3) – Enter comment or nick name; you can use this to distinguish between multiple keys.

Step (4) – Enter Strong Key Password and Set Expiration Date. Expiration date can be set like

- y for year, e.g. 1y for 1 year
- w for weeks, e.g. 2w for 2 weeks
- d for days, e.g. 4d for 4 days

Step (5) – Select key size from dropdown; larger key sizes are more secure.


Step (6) – Click Generate Key; it will take a few minutes to generate your key.

Import a Key

If you already have a key pair in your local computer, then you can import them to your cPanel. You can only import the Public Key.

To import a GnuPG key, follow these steps:

Step (1) – Scroll down to find Import Key in Encryption Interface.



Step (2) – Click on the Import Key Button. You will be taken to a new interface.

Paste the GPG or PGP data below.

```

-----BEGIN PGP PUBLIC KEY BLOCK-----
Version: GnuPG v2.0.14 (GNU/Linux)

mQGIBFamJxARBADVgMFRVjEa9Du68EwIQ55iTbatBZyutr4pUycsTx1seOyXzx
X
G+EqT/cWVc8VuwJVUsd6lw6ATQa7QhUBZjedVFIqt3N9UUymeLrv/tFiDUtxMGfC
2Z6X6cPKmd0LmxQij+qaHPD6ECRoyM303IHs4zqliylpHk7H68
/Qg0KbQwCg1F5t
jS+kAYWWomBCbxok2m5jqosD/iD9iWr5pjt1jx3fHHS8H9icPA3Dn7Tjp+Mr841Z
4dCHBIZFWzrFEYTp4ouWexqFGETwb71id3svvgg+UQdVIObeUzW6E6Gdtck9sGjj
k
fWZYiq
/T9eRs703oFuxGvnXMAN6bYQGtzwqztOtbTkDoMj+QGyR7jRtgipnX6HBm
z3KHBACzaLm2mfSJL/AiXHYfEJTU3kljad2juvOGREDi4gxG6xAVwjxrEMSkisAs
iny2pVGLwXthlvnKg18y4q2lucwRmK2fy0aa2PKrQIsaq+2DPSg6i6qvfYzs0ZH2
WQuji/pL4Fs7JksUteRc0s0afRVfiX+8Q7kGILRLWpnHlOr0zqrQwVHV0b3jpyWxz

```

[Import](#)

Step (3) – Paste your Public key in the text box; make sure it includes both the header and footer rows.

Step (4) – Click the Import button to import the key.

Delete or View the Key

To delete or view a public or private key from your cPanel, follow these steps:

Step (1) – Scroll down in Encryption Interface to find the list of keys.

Public Keys	
Public Keys	Actions
F89C70E9 [1024D] Tutorials Point (Info) (info@tutorialspoint.com)	Delete GnuPG Key View

Private Keys	
Private Keys	Actions
F89C70E9 [1024D] Tutorials Point (Info) (info@tutorialspoint.com)	Delete GnuPG Key View

Step (2) – To view a key, click View corresponding to the Key you want to view.

Step (3) – To delete a key, click Delete GnuPG key, it will ask for confirmation, click yes to delete the key.


43. cPanel – Apache Spamassassin

Apache Spamassassin is a software integrated into the cPanel, which helps to prevent getting spam messages in your mailbox. It helps in preventing your mail box to get flooded with spam messages. When Apache Spamassassin is enabled, it rates every message by a spam score. You can choose the spam emails to auto delete according to spam score. If you choose auto spam deletion with spam score of 5, then all emails having 5 or more spam score will be deleted automatically.


Enable or Disable Apache Spamassassin

To enable Apache Spamassassin, use the following steps:

Step (1) – Click on Apache Spamassassin link found under the Email section of cPanel Home.



Step (2) – If Apache Spamassassin is currently disabled, then you can enable it by clicking Enable Apache Spamassassin. If it is already enabled, you can disable it by clicking Disable Apache Spamassassin.



Setup Spam Auto-Delete

To setup Spam Auto-Delete, follow these steps:

Step (1) – Find Filter options in Apache Spamassassin Interface.

Filters

Spam Auto-Delete is Enabled

Messages with a Spam score of "5" or higher will be deleted.

You can automatically delete messages that the system marks as spam. First, set the number of hits that you wish to require before the system marks mail as spam.

NOTE: 5 is the default setting. The higher the number, the more conservative the setting.

Score

You may also disable auto-deletion of spam.


Step (2) – Select Spam score from dropdown between 1 to 10. Lower score is stricter, while higher score is more permissive. This means score 1 will filter many emails and will delete most of the emails you receive and score 10 will allow more emails to pass through the filter.

Step (3) – Click Auto-Delete Spam to enable automatic spam deletion based of your chosen score.


To disable automatic spam deletion, click Disable Auto-Delete Spam.

44. cPanel – Visitors

This interface of cPanel allows you to view the statics and analytics for your domains. These simple metrics feature helps you to get the idea about your performance and optimize the quality of your websites.



Step (1) – Click on Visitors icon under Metrics section of cPanel Home. You will see the list of domains available.



Step (2) – For details related to a particular domain, just click **View** indicated right after the domain name.

Latest visitors to "umeshkumhar.xyz".

Reporting Period: 2/6/16 10:47 PM - 2/7/16 4:48 PM
Total Data Sent: 1.62 MB

359 records match.

IP	URL	Time	Size (bytes)	Referring URL
199.21.99.205	/	2/7/16 4:48 PM	7240	
125.19.102.78	/wp-content/uploads/2015/12/3578.gif	2/7/16 4:43 PM	3423	https://umeshkumhar.xyz/profile/admin-ajax.php?action=dynamic_css
125.19.102.78	/umeshkumhar/img/icons/blog-icon.svg	2/7/16 4:43 PM	1327	https://umeshkumhar.xyz/umeshkumhar/css/style.css
125.19.102.78	/umeshkumhar/img/icons/mail-icon.svg	2/7/16 4:43 PM	568	https://umeshkumhar.xyz/umeshkumhar/css/style.css
125.19.102.78	/umeshkumhar/img/icons/icon-close-desktop.svg	2/7/16 4:43 PM	438	https://umeshkumhar.xyz/umeshkumhar/css/responsive.css
125.19.102.78	/img/img-1-large.jpg	2/7/16 4:43 PM	3371	https://umeshkumhar.xyz/
125.19.102.78	/module/3b0d8766/images/ajax-loader.gif	2/7/16 4:43 PM	847	https://umeshkumhar.xyz/

Here the obtained table is divided in five columns i.e. IP (Internet Protocol), URL, Time, Size, Referring URL.

IP (Internet Protocol): The IP address of the visitor network computer.


URL: It refers to the full URL of the page content.

Timestamp: The date and time when the user visits the particular URL.


Size: The bytes consumed by the user for loading the URL content.

45. cPanel – Errors

This function will display the last 300 errors for your site. This can be very useful for finding broken links or problems with missing files. Checking this log frequently can help keep your site running smoothly. This can help you to debug your website errors.



It will take you to the following interface.




This list of the errors occurred on this domain related to any issues. In this case there are no errors on this domain. You can frequently check this error log to see if there are any errors related to your website. It will be helpful for you to troubleshoot and resolve the errors.

46. cPanel – Bandwidth


This function allows you to see the bandwidth usage for your site. It shows the current month's bandwidth usage, as well as your total bandwidth usage. This will include all HTTP (web) and POP (mail) bandwidth usage, and may include FTP bandwidth usage, if your system administrator has enabled FTP bandwidth logging.



Click the Bandwidth icon and it will take you to an interface. Here, in this interface, you are provided with the monthly bandwidth transfer and represented in form of graphs. This graph is able to display the bandwidth consumed by HTTP, FTP services. This is available in three forms – past 24 hours, past week, past year.




Also, this representation is in the form of pie charts that is on a monthly basis. This data is beneficial to get an idea about the traffic coming in to that domain.




47. cPanel – Webalizer

Webalizer is a complex statistics based program, which produces a variety of charts and graphs about who has visited your website. This is a sort of analyzer that shows you the data in the form of graphs and pie charts.



Here is a Webalizer interface of the domain listing –



Also the representation is in form of pie charts that is on a monthly basis. This data is beneficial to get an idea about the traffic to the domain. The data values consists of the visits, hits, files, pages that the users have accessed.

Usage Statistics for umeshkumar.xyz

Summary by Month
Generated 06-Feb-2016 22:19 IST


Usage summary for umeshkumar.xyz

Month	Hits	Files	Pages	Visits	Sites	KBytes	Bytes	Hits
Mar	0	0	0	0	0	0	0	0
Apr	0	0	0	0	0	0	0	0
May	0	0	0	0	0	0	0	0
Jun	0	0	0	0	0	0	0	0
Jul	0	0	0	0	0	0	0	0
Aug	0	0	0	0	0	0	0	0
Sep	0	0	0	0	0	0	0	0
Oct	0	0	0	0	0	0	0	0
Nov	105	47	19	105	19	26336	114	1203
Dec	383	82	22	383	22	324251	544	19604
Jan	608	72	24	608	24	208968	744	14377
Feb	343	200	47	343	47	26336	114	1203
Totals	559555	1402	452	559555	452	35184	61753	


Generated by [Webalizer Version 2.23](#)

48. cPanel – Raw Access

Raw Access Logs allow you to see who has visited your website without displaying graphs, charts, or other graphics. You can use the Raw Access Logs menu to download a zipped version of the server's access log for your site. This can be very useful when you want to quickly see who has visited your site.




Here is the Raw Access interface of domain listing –




Here, the management of Raw Logs takes place. The archived logs are available for downloads. You can also configure to remove or archive the raw logs for domains.

49. cPanel – CPU and Connection Usage

To access your CPU and Concurrent connection usage, click CPU and Concurrent Connection usage under Metrics section of the cPanel home.




This is the interface of resource usage overview –



How virtual memory resources are utilizing is represented in the form of graphs and tabular data. The CPU usage with the utilization of the memories. The number of processes taking place with their usage, limit and fault data values. The input/output usage, processors, physical memory, virtual memory, processes and faults are represented as per their usage limits.

From	To	USAGE																					
		CPU			vMEM(MB)			pMEM(MB)			EP	nPROC			IO(KB/s)			vMf	pMf	EPf	nPf		
		a	m	l	a	m	l	a	m	l	a	m	l	a	m	l							
02-08 16:30	02-08 17:30	0	0	100	0.65	422.77	1024	0.11	45.48	1024	0	1	20	0	1	100	0	187	1024	0	0	0	0
02-08 17:30	02-08 18:30	0	0	100	0.03	23.10	1024	0.03	23.17	1024	0	1	20	0	1	100	0	0	1024	0	0	0	0
02-08 18:30	02-08 19:30	0	20	100	0.00	0.00	1024	0.01	10.05	1024	0	0	20	0	0	100	0	4	1024	0	0	0	0
02-08 21:30	02-08 22:30	0	20	100	0.08	47.65	1024	0.10	46.70	1024	0	1	20	0	1	100	0	378	1024	0	0	0	0
02-09 01:30	02-09 02:30	0	20	100	1.57	1024.00	1024	0.18	49.89	1024	0	1	20	0	1	100	0	193	1024	4	0	0	0
02-09 02:30	02-09 03:30	0	20	100	0.06	43.80	1024	0.13	48.05	1024	0	1	20	0	1	100	0	11	1024	0	0	0	0
02-09 03:30	02-09 04:30	0	0	100	0.06	43.94	1024	0.07	43.62	1024	0	1	20	0	1	100	0	1	1024	0	0	0	0
02-09 04:30	02-09 05:30	0	0	100	0.00	0.00	1024	0.05	9.80	1024	0	0	20	0	0	100	0	3	1024	0	0	0	0
02-09 06:30	02-09 07:30	0	0	100	0.00	0.00	1024	0.02	9.73	1024	0	0	20	0	0	100	0	2	1024	0	0	0	0
02-09 07:30	02-09 08:30	0	20	100	0.02	8.61	1024	0.05	15.71	1024	0	0	20	0	2	100	0	60	1024	0	0	0	0
02-09 08:30	02-09 09:30	0	0	100	0.00	0.00	1024	0.01	9.92	1024	0	0	20	0	0	100	0	2	1024	0	0	0	0
02-09 09:30	02-09 10:30	0	20	100	0.03	22.61	1024	0.07	22.93	1024	0	1	20	0	1	100	0	24	1024	0	0	0	0
02-09 10:30	02-09 11:30	0	20	100	1.85	1024.00	1024	0.13	43.18	1024	0	1	20	0	1	100	0	156	1024	2	0	0	0
02-09 13:30	02-09 14:30	0	0	100	0.00	0.00	1024	0.01	10.93	1024	0	0	20	0	0	100	0	64	1024	0	0	0	0
02-09 14:40	02-09 14:41	0	0	100	0.00	0.00	1024	0.86	10.39	1024	0	0	20	0	0	100	1	19	1024	0	0	0	0




50. cPanel – IP Blocker

cPanel IP blocker enables you to block your website for a single IP address, domain name or a range of IP address. All those users, who will try to access your website from blocked IP addresses will not be able to access your website. You can manually deny those IP addresses, who are using your website's bandwidth or doing malicious activity.


Deny Access to an IP Address or Domain

To deny access to a specific IP address or Domain name, follow these steps:

Step (1) – Open cPanel IP Blocker by clicking on the IP Blocker Link found under the security section of cPanel Home.



Step (2) – In Add an IP or Range, enter your IP address or Domain Name or Range.



IP address can be entered in the following formats.


- Single IP address, E.g. 192.168.0.1
- IP address Range, E.g. 192.168.0.1–192.168.0.100 or 192.168.0.1–100
- CIDR format, E.g. 192.168.0.1/32
- Using Wildcard, E.g. 192.168.*.*
- Domain Name, google.com

Step (3) – Press Add Button to block that IP address or Range to access your website.

Remove an IP from the Denied List

You can allow access to a denied IP address or Range, by following these steps:

Step (1) – Open cPanel IP Blocker by clicking on IP Blocker Link found under security section of cPanel Home.



Step (2) – Scroll down to find Currently-Blocked IP Addresses. Find the IP address or Range you want to remove, and click on Delete link.

Currently-Blocked IP Addresses:			
Server Setting	Beginning IP	Ending IP	Actions
192.168.0.1	192.168.0.1	192.168.0.1	Delete
192.168.0.2/31	192.168.0.2	192.168.0.3	Delete
192.168.0.4/30	192.168.0.4	192.168.0.7	Delete
192.168.0.8/29	192.168.0.8	192.168.0.15	Delete

Step (3) – It will ask you for confirmation, click on Remove IP. It will remove the IP from blocked list and will give back the permission to access your site.

51. cPanel – SSH / TLS


SSL (Socket Security Layer) or TLS (Transport Layer Security) is a mechanism for encrypting data, which is transferring from your computer to host or server and vice versa.

Generate Private Key


Private Key resides at your server and decrypts the incoming data coming from visitor's device. Without Private Key, your server will not be able to decode the data sent by user. Private Key is automatically generated when generating a CSR.

To generate a Private Key, follow these steps:

Step (1) – Open cPanel SSL/TLS manager, by clicking on SSL/TLS found under the security section of cPanel.



Step (2) – In Private Keys, click on **Generate, view, upload, or delete your private keys.**



Step (3) – You can use Generate a New Private Key Interface to generate a new key.

Generate a New Private Key.

You should generate a new key file for each certificate you install. A key size of 2,048 bits is recommended.

Key Size

2,048 bits (Recommended)

Description:

Optional: You can use this field to provide a description for this private key.

Step (4) – Choose a Key Size from the dropdown menu. Provide a description which is optional, you can leave it blank.

Step (5) – Click on Generate Button to generate a new private key.

Upload a Private Key

To upload a Private Key to your server, you can use the interface below to Generate a New Key Section, which is Upload a New Private Key. Just paste your existing key into textbox and provide a description. Then click Save to import the key.

Upload a New Private Key.

If you have an existing key, paste the key below, or upload it to the server.

Paste the key into the following text box:

Description:

Optional: You can use this field to provide a description for this private key.

Or if you have an existing private key in '.key' file, you can also import it. Just scroll down to choose a **.key** file under Upload a New Private Key. Browse for the file and select it. Click Upload button to Import the key into server.

Choose a .key file.:

No file selected.

Description:


Optional: You can use this field to provide a description for this private key.

Generate a CSR


CSR (Certificate Signing Request) is an encoded certificate, which CA authorities ask for when we purchase a SSL certificate from them. To issue a SSL certificate they need some additional information, which we provide in the CSR.

To generate a CSR, follow these steps below.

Step (1) – Click SSL/TLS link found under Security section of the cPanel.



Step (2) – Under Certificate Signing Request (CSR) click Generate, view, or delete SSL certificate signing requests.



Step (3) – In SSL Certificate Signing Request Interface, scroll down to see Generate a New Certificate Signing Request (CSR).

Generate a New Certificate Signing Request (CSR)

Use this form to generate a new certificate signing request for your domain. Your SSL certificate authority (CA) will ask for a certificate signing request to complete the certificate purchase. Your CA may require specific information in the form below. Check with the CA's CSR requirements for the Apache web server.

Key*

Generate a new 2,048 bit key.

Domains *

Provide the FQDNs that you are trying to secure, one per line. You may use a wildcard domain by adding an asterisk in a domain name in the form: *.sample.com. NOTE: Many CAs charge a higher price to issue multiple-domain certificates (sometimes called "UCCs" or "SAN certificates") and certificates that include wildcard domains.

City*

Provide the complete name for the city or locality. Do not use abbreviations.

Step (4) – Choose an existing Private Key from Key dropdown. You can also choose to generate a new Private Key.

Step (5) – Enter Domains for which you want to generate CSR. You can choose a wild card domain by putting * as a subdomain. E.g. *.tutorialspoint.com.

Step (6) – Provide all necessary information in text fields like City, State, Country, Company etc.

Step (7) – Click Generate Button to generate a CSR.

Upload an SSL/TLS Certificate

If you have obtained an SSL/TLS certificate from a Trusted Certificate Provider, then you will need to upload it to your server to use it on your website.

To generate Upload a SSL/TLS certificate, follow these steps below:

Step (1) – Click on SSL/TLS link found under Security section of cPanel.

Step (2) – Under Certificates (CRT), click on Generate, view, upload, or delete SSL certificates.



Step (3) – Scroll down to Upload a New Certificate, paste your SSL/TLS code in textbox and click Save Certificate or Upload a .crt file, which will be provided by hosting provider and Click Upload Certificate.

Upload a New Certificate

Use this form to upload a certificate provided by a third-party Certificate Authority. You may either paste the body of the certificate or upload it from a ".crt" file.

Paste the certificate into the following text box:

Description

[Save Certificate](#)

or

Choose a certificate file (*.crt).

[Browse...](#) No file selected.

Description

[Upload Certificate](#)

Self-Signed Certificate

You can also use a self-signed certificate on your website too, but when somebody will open your website, it will show an error that the certificate is not from a trusted certificate provider. It is recommended that in production environment, you use a purchased SSL/TLS certificate.

To Generate a Self-signed Certificate, you can follow these steps.

Step (1) – Scroll down to Generate a New Certificate in Certificates section.

Generate a New Certificate

Use this form to generate a new, self-signed certificate for your domain. Typically, self-signed certificates are temporarily used until you receive a trusted SSL certificate from your SSL certificate authority.

Key*

Generate a new 2,048 bit key. ▼

Domains*

Provide the FQDNs that you are trying to secure, one per line. You may also use wildcard domains by adding an asterisk in a domain name in the form: *.sample.com. (Certificates with multiple domains are sometimes called "UCCs" or "SAN certificates".)

City*

Provide the complete name for the city or locality. Do not use abbreviations.

Step (2) – Choose an existing Private Key from Key dropdown, you can also choose to generate a new Private Key.

Step (3) – Enter Domains for which you want to generate CSR, you can choose a wild card domain by putting * as a subdomain. E.g. *.tutorialspoint.com.

Step (4) – Provide all necessary information in text fields like City, State, Country, Company etc.

Step (5) – Click Generate to generate a Certificate.

Installing SSL


To activate SSL/TLS certificate in your domain or Subdomains follow these steps:

If you have obtained a SSL/TLS certificate from a Trusted Certificate Provider, to use it on your website, you will need to upload it to your server.


To generate Upload a SSL/TLS certificate, follow these steps below.

Step (1) – Click SSL/TLS link found under Security section of cPanel.

Step (2) – Under Certificates (CRT), click Install and Manage SSL for your site (HTTPS).



Step (3) – In this interface, you can choose to install SSL in your website. Scroll down to install an SSL Website.



Step (4) – Choose a certificate from the installed certificates by clicking on Browse Certificates. At the same time, you can also select a Domain from the dropdown box and Click Autofill by Domain.

Step (5) – All fields of Certificates, Private Key and Certificate Authority bundle will be filled automatically.


Step (6) – Click Install Certificate button to activate the certificate for the Domain or Subdomain.

52. cPanel – Hotlink Protection


Hotlink Protection prevents other websites to directly load data from your website. For example, when somebody links an Image on your website to load up on his website, when a visitor visits the other website, the image is loaded from your website consuming your bandwidth. Hotlink protection enables prevention against this. If Hotlink Protection is Enabled, other websites will not be able to directly link to any file on your website.

To use this feature, follow these steps:

Step (1) – Open cPanel Hotlink Protection by clicking on Hotlink Protection found under Security section of cPanel home.



Step (2) – Click on Enable button on Hotlink Protection Interface to enable Hotlink Protection.



Configure Hotlink Protection

You can configure Hotlink Protection to give access to those URLs, which you want, those URLs can link to your files directly. Additionally, you can provide the extensions of those files, which you want to protect via Hotlink Protection.

To configure Hotlink Protection, scroll down to Configure Hotlink Protection on Hotlink Protection Interface.

URLs to allow access: Enter those URLs here, whom you want to grant permission to directly access your website's files.

Block direct access for the following extensions (comma-separated): Enter those file extensions here, which will not be able to be linked by other website. For E.g. MP4, JPG, and PNG etc.

Allow Direct Requests: This will allow the user to access your files directly by providing full URL of your file. For example, when a visitor will enter the full URL

of a PDF file, the file can be viewed in a browser. It is recommended that you select this checkbox.

Redirect the request to the following URL: If a website tries to link to a file directly from your website, the system will redirect that URL to the one provided in this field.

Configure Hotlink Protection:

URLs to allow access:

Block direct access for the following extensions (comma-separated):

Allow direct requests (for example, when you enter the URL of an image in a browser).
NOTE: You *must* select the "Allow direct requests" checkbox when you use hotlink protection for files that you want visitors to view in QuickTime (for example, Mac Users).

Redirect the request to the following URL:


Click Submit to update the changes you made.

53. cPanel – Ruby on Rails


This interface of cPanel allows you to create and Install a Ruby on Rails application. If you have a Ruby on Rails application developed, you can deploy it to your server using this interface.

To Create a Ruby on Rails Application, follow these steps:

Step (1) – Click Ruby on Rails found under Software Section of cPanel Home.



Step (2) – In Ruby on Rails Interface, you will find Create Ruby on Rails Application.

A screenshot of the 'Ruby on Rails' application creation interface. It features a title 'Ruby on Rails' with a logo, a brief description, and a 'Create Ruby on Rails Application' section. The form includes fields for 'App Name' (containing 'My App'), 'Application Path' (containing 'rails_apps/MyApp'), and 'Environment' (a dropdown menu set to 'production'). There is also a checkbox for 'Load on Boot?' and a 'Create' button.

Step (3) – Provide name of your application in App Name.

Step (4) – Provide a Path for your application in your Home Directory.

Step (5) – Choose appropriate environment for your Application. Select Load on Boot, if you want your application to automatically start, whenever your server starts.

Step (6) – Click Create to create a new Ruby on Rails Application.

To delete a Ruby on Rails Application, you can scroll down to the list of currently Available Ruby on Rails Application.

Available Ruby on Rails Applications							
App Name	Path	Rails Server	App Status	Actions	Load on Boot?	Production	Actions
My App	/rails_apps/MyApp	URL	not running	▶ Run ■ Stop	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	🗑 Delete

Click Delete link from Action button to delete the application. You can also change the preferences of application from this interface.

Create a Rewrite

Ruby on Rails applications run on a different port rather than the incoming traffic. People will access port number 80 or 443, which is for http and https, and hence you will need to redirect people from that port on to which Ruby on Rails application is running. To create a rewrite, scroll down on Ruby on Rails Interface to Create a Rewrite. Click Create Rewrite link next to the app name of which you wish to create the rewrite.

Create A Rewrite	
App Name	Action
My App	+ Create Rewrite

It will take you to the following interface.

Create a URL Rewrite

Since applications are running on a different port than the other URLs on your server, you'll need to redirect incoming traffic to that port. To do this, you can create a URL rewrite to send users to your Ruby on Rails application.

i Requests will be rewritten to <http://tutorialspoint.com:12006>.

App Name
My App

Domain

URL

Choose a domain from the dropdown and if you want, you can specify a URL for that too in the URL text box.

Click Save to create a rewrite.


54. cPanel – Optimize Website

This interface of cPanel helps you to enable **gzip** compression. Apache allows you to compress the data before sending it to the browser and then web browser extracts the data and displays the webpage. All modern browsers support gzip compression. This gzip compression needs Apache **mod_deflate** to function currently, which is available in most cPanel installed Linux servers. This compression is very useful, because it helps in compressing data hence our bandwidth is saved, plus it makes our website to load much faster.


You can compress specific types of MIME (Multipurpose Internet Mail Extensions) or you can compress all the files using this interface.

To enable gzip compression, follow these steps:

Step (1) – Open cPanel Optimize Website interface by clicking on Optimize Website link in the Software section of cPanel.



Step (2) – In Optimize Website, you will see Compress Content.



You can choose from the following –

- Choose Disable to disable gzip compression.
- Choose Compress All Content to enable gzip compression for all content.
- Choose Specified MIME types and provide MIME types in text box. MIME type are similar to file types. It has both file type and file format information separated with a slash. E.g. text/javascript, text/css, image/jpg, image/png etc.

Step (3) – Click Update Settings to update the settings.


55. cPanel – Cron Jobs

If you want to run a command or a **php program** on a specified time interval like once a day or once a week, you can setup **cron jobs** in this interface. Cron jobs allow you to run a specific command or program automatically. This is often required, if you are using a software like CRM or Billing Software. Setting up cron jobs more often may degrade your server's performance.

Setup Cron Job

To add a new cron job, follow these steps:

Step (1) – Open Cron Jobs by clicking Cron Jobs found in the Advanced section in cPanel.



Step (2) – Scroll down to see Add New Cron Job interface.

Add New Cron Job

Common Settings

-- Common Settings --

Minute:
/15 Once Per Fifteen Minutes(/15)

Hour:
* Every Hour (*)

Day:
* Every Day (*)

Month:
* Every Month (*)

Weekday:
* Every Day (*)

Command:
php /home/tutorialspoint/public_html/cron.php

Add New Cron Job

Step (3) – You can choose an existing setting from common settings. If you do that all the fields of cron execution time will automatically get filled. Or you can choose your custom runtime settings by specifying in the next text inputs accordingly.

Step (4) – Enter your command to run in cron job. If you are running a php file, enter full name of php file. For example –

```
php /home/tutorialspoint/public_html/cron.php
```

Step (5) – Click Add New Cron Job button to add a cron job.

Cron Email

cPanel by default sends an email each time a cron job runs. It also redirects the output of the command or file into the email. Default email for this is your system account, but you can change this email too. To change the email on which you want to receive cron email, firstly find out Cron Email interface in Cron Jobs. Then enter your new email in which you wish to get cron emails. Click Update email to update your email.

Cron Email

Send an email every time a cron job runs. [less »](#)

You can have cron send an email everytime it runs a command. If you do not want an email to be sent for an individual cron job you can redirect the command's output to /dev/null like this:
`mycommand >/dev/null 2>&1`

Current Email
tutorialspoint

Email

[Update Email](#)

If your cron runs more frequently, then you may not want to receive emails, you can disable receiving emails by redirecting your output into null by writing `>/dev/null 2>&1` at the end of the command. For example –

```
php /home/tutorialspoint/public_html/cron.php >/dev/null 2>&1
```

Edit or Delete Existing Cron Jobs

To edit or delete your existing cron jobs, you can scroll below on the Cron Jobs interface to see current cron jobs. Once you select the job, you can click either the delete link or the edit link to edit or delete a particular cron job.

Current Cron Jobs						
Minute	Hour	Day	Month	Weekday	Command	Actions
*/15	*	*	*	*	php /home/tutorialspoint/public_html/cron.php	Edit Delete

56. cPanel – Track DNS


You can use this interface of cPanel to find out the general DNS of a domain. It will give you the IP address of that domain, mail servers and raw DNS information. This can be useful to retrieve network information.

Domain Lookup

This tool retrieves the IP address of the domain and displays email hosts used by the domain. It also displays the raw DNS data of the domain.

To lookup a domain, use the following steps:

Step (1) – Open cPanel Track DNS by clicking Track DNS link found under the Advanced section of cPanel.



Step (2) – In the Domain lookup interface, enter the domain, which you want to look up.


Domain Lookup

The Domain Lookup tool allows you to find out the IP address of any domain, as well as DNS information about that domain. This can be a very useful tool right after your site is set up or after DNS changes have been made to make sure your DNS is setup properly.

Enter a domain to look up:

Step (3) – Press Look Up button to lookup a DNS of a domain.

You will get information in the following manner.



Track DNS

tutorialspoint.com has address 72.21.91.8
 tutorialspoint.com mail is handled by 5 alt2.aspmx.l.google.com.
 tutorialspoint.com mail is handled by 10 alt3.aspmx.l.google.com.
 tutorialspoint.com mail is handled by 10 alt4.aspmx.l.google.com.
 tutorialspoint.com mail is handled by 1 aspmx.l.google.com.
 tutorialspoint.com mail is handled by 5 alt1.aspmx.l.google.com.

Zone Information

```

; <<> DIG 9.8.2rc1-RedHat-9.8.2-0.37.rc1.el6_7.6 <<> tutorialspoint.com
;; global options: +cmd
;; Got answer:
;; ->HEADER<<- opcode: QUERY, status: NOERROR, id: 36593
;; flags: qr rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 0

;; QUESTION SECTION:
;tutorialspoint.com.      IN      A

;; ANSWER SECTION:
tutorialspoint.com.     2295   IN      A      72.21.91.8

;; Query time: 36 msec
;; SERVER: 8.8.8.8#53(8.8.8.8)
;; WHEN: Wed Feb  3 00:39:36 2016
;; MSG SIZE  rcvd: 52
  
```

The top-most line provides the IP address of the domain. The other following lines tells about the mail servers. In Zone Information, you will see the raw DNS information of the domain.

Trace Route

Another function in cPanel Track DNS is the trace route. This function of Track DNS gives you information of the route between the computer in which the user is logged in and the server, where your website is hosted.

Trace Route

This function allows you to trace the route from the computer you are accessing cPanel from to the server your site is on (i.e. the number of servers and what servers your data must pass through to get to your site).


To trace the route of your computer and the server, scroll down to see Trace Route interface. Click Trace to get the information of the route between your webserver and you.

57. cPanel – Indexes


You can customize the way a directory looks in your website. By default, cPanel displays the list of files and directories, if there is no index file in that directory. You can choose the way it displays the list of contents in the front-end. You can also choose to disable the indexing of files in that directory by choosing **No Indexing**.

To manage cPanel Indexes, follow these steps:

Step (1) – Open cPanel Index Manager by clicking on Indexes found under Advanced section of cPanel Home.



Step (2) – You can select a directory of which you wish to manage indexes by clicking over the name of directory. To navigate within directories, you can click on the folder icon corresponding to that directory to open up the directory.



Step (3) – Once you have selected the directory, you will be given some options to choose from.

- **Default System Indexing** – Enables the default setting your hosting provider setup for you.
- **No Indexing** – This option will disable the directory listing and if there is no index file such as index.php or index.html in the directory. User will get an error.
- **Standard Indexing** – This option will enable the directory listing and user will see the name of the directories.

- **Fancy Indexing** – This option will enable the directory listing and user will see the name and description of the files and directories under your indexed directory.

Set Indexing for `"/home/liptanxy/public_html"`

Default System Setting

No Indexing

Standard Indexing (filename only)

Fancy Indexing (filename and description)

Step (4) – Click Save to save your choice for that directory. If successful, you will see a success message.


58. cPanel – Error Pages

When visitors browse your website and there is some problem accessing your website, your webserver automatically provides a basic error page. A Basic error page shown by apache webserver, when an error is encountered.


A Basic page contains the error code and error message only. You can customize this error page according to your choice. Each problem your webserver encounters has a unique error code; your webserver displays the error accordingly.

To modify an error page, follow these steps:

Step (1) – Open cPanel Error Pages interface by clicking on Error Pages link found in the advanced section of the cPanel Home.



Step (2) – In Error Pages interface, select the domain or subdomain for which you want to configure the error pages from the drop down menu.



Step (3) – Select the error code of which you wish to edit the error page. You can choose from the Common Error codes or you can click All HTTP error codes to see the list of all error codes.


403.shtml (Forbidden)

You are editing the error pages for the domain "tutorialspoint.com".

Select Tags to Insert:


</> Referring URL </> Visitor's IP Address </> Requested URL

</> Server Name </> Visitor's Browser </> Redirect Status Code



The screenshot shows a web editor interface. At the top, there's a title "403.shtml (Forbidden)" and a subtitle "You are editing the error pages for the domain 'tutorialspoint.com'". Below that, it says "Select Tags to Insert:" followed by six clickable tags: "</> Referring URL", "</> Visitor's IP Address", "</> Requested URL", "</> Server Name", "</> Visitor's Browser", and "</> Redirect Status Code". Below the tags is a text area with a toolbar and the placeholder text "<!-- Enter your code here >".

Step (4) – It will open an HTML editor for you in which you can enter the HTML code for the error page you selected. You can also use predefined tag in your code, click on the tag to insert it to the editor.



The screenshot shows the bottom part of the HTML editor. It features a status bar with "Position: Ln 1, Ch 27" and "Total: Ln 1, Ch 27". Below the status bar is a blue "Save" button.

Step (5) – When finished inserting the code in the editor, Press Save button to save the error page. Now each time your visitor will encounter the error, he will be served your custom error page.


59. cPanel – MIME Types

MIME (Multi-Purpose Internet Mail Extensions) types tell the browsers how to handle certain types of files. When a file is sent to a browser of your website's visitor, it also sends the MIME type of that file with that too. The MIME type tells the browser about the type of file and how the file will be served to the user. For example, if a **.js** file is sent to the browser then application/JavaScript MIME type is also sent to tell the browser that the .js file is a JavaScript file, and browser handles the file accordingly.


Most of the MIME type are defined in a system defined MIME types. But if you have a file with custom extension, you can specify MIME type for that file in this interface. This will tell the browser about your custom extension and how to handle that file.

To add a custom MIME type, please follow these steps:

Step (1) – Open cPanel MIME Types by clicking on MIME Types in Advanced Section of cPanel.



Step (2) – In Create A MIME Type interface, Enter your MIME type.

A screenshot of the 'Create A MIME Type' interface. The title 'Create A MIME Type' is at the top. Below it, there are two input fields. The first is labeled 'MIME Type' and contains the text 'text/batchfile'. The second is labeled 'Extension(s)' and contains the text '.bat'. Below the second field is a tip: 'Tip: Separate multiple extension types with a space.' At the bottom left of the form is a blue 'Add' button.

Step (3) – Enter the extension for your file. If you have multiple extensions, you can add all of them at once by separating them with a space.

Step (4) – Click on Add button to save the custom MIME type.

Delete a MIME Type

You can only delete the MIME Types defined by you. As, you are not allowed to delete the MIME types, which are defined by the System automatically. To delete a MIME type, Scroll down to the User Defined MIME Types and Click Delete link corresponding to the MIME type you want to delete.

User Defined MIME Types		
MIME Type	Extension(s)	Actions
text/batchfile	.bat	Delete


It will ask for confirmation; click Delete MIME Type to delete a user defined MIME type.

60. cPanel – Virus Scanner


Many cPanel web hosting comes with this ClamAV virus scanner feature to guard against potential threats on your server. You can run on-demand scan of your files to see if they are infected with any virus or not. ClamAV is an open source powerful antivirus, it uses its extensive database to detect several types of potential threats like viruses, Trojan horses, malwares, malicious scripts etc.

You can scan different sectors of your home directory using the antivirus. To scan your account with a virus scanner, use the following steps:

Step (1) – Open cPanel Virus Scanner by clicking the Virus Scanner link in the Advanced section of the cPanel home.




Step (2) – You can choose the scan type from here.



- **Scan Entire Home Directory** – This option will scan your entire cPanel account. If you choose this option, no need to run the scan on other options. This will scan your home directory, which contains the Emails, FTP accounts and Website.
- **Scan Mail** – This option will scan your emails for viruses. If somebody sends a malicious email having some virus or malware, this virus scanner will tell you that.
- **Scan Public FTP Space** – This option will scan your public_ftp folder. If somebody uploaded a malicious file through FTP, virus scanner will find it.
- **Scan Public Web Space** – This option will scan your public_html in which all your front end files reside.

Step (3) – Click Scan Now button to start the scan and it will automatically show you the results.




The screenshot displays the 'Virus Scanner' interface in cPanel. At the top, there is a search icon and the title 'Virus Scanner'. Below this, a status message reads 'Scanning: ... scan complete 398 files scanned.' The interface is divided into several sections: 'File' with input fields for '396' and '398'; 'Data' with input fields for '1 MB' and '1 MB'; 'Scanner Progress' featuring a full-width progress bar and a '100 %' indicator; and 'Infected Files' which is an empty scrollable list box.

If the Virus Scanner finds any malicious software, then it will give you options to correct the error. You may choose the option accordingly.


61. cPanel – Softaculous Apps Installer

Softaculous Apps Installer is an auto script installer, which installs the most popular PHP, JavaScript, Perl applications in just a few clicks. When using Softaculous Apps Installer, you will not need to manually install applications by first uploading the files and then creating the database and finally installing them. But you can install them in a few clicks.

To access Softaculous Apps Installer, you can find the Softaculous Apps Installer link in the Software section of the cPanel Home.




You can also find a dedicated section of Softaculous Apps Installer in the cPanel home, which displays the most popular applications and the application category in the front panel.




You can install the applications, modify the installation and Create as well as Manage Backups.

When you will click on Softaculous Apps Installer in the Software section, it will take you to the App installer interface like shown below.



Install Application using Softaculous Apps Installer


To install an application from the Softaculous Apps Installer search from the search box given at left or click on any of the categories. Then you can select the application you wish to install.




Click Install and follow the instructions that follow to install the application directly into your website.

Create Backup of any Application


You can easily create a backup of your application using the Softaculous Apps Installer to restore it in your account later. To create the backup of your application, you will need to go to the list of all installations section of your Softaculous Apps Installer. Click on the icon at the top of the navigation bar to open All Installations.



In All Installations, you will find the list of all applications, which are installed by the Softaculous Apps Installer.



Click on the Backup icon to create an automatic backup of the whole application installation. This backup will include all the files, database and configuration of the application. You can always restore the application by going into Backup and Restore interface of Softaculous Apps Installer, which can be opened by clicking on Backup and Restore icon from the top navigation menu.



62. cPanel – Installing WordPress

You can directly install WordPress in your website by making a few clicks through the Softaculous Apps Installer. WordPress is a very popular content management software as more than a million websites are powered by it. It's secure, reliable, easy to use and totally customizable. To install WordPress using Softaculous Apps Installer, follow these steps.

Step (1) – In the left menu click Blogs and you will find WordPress. Click on that and follow the instructions.



Step (2) – It will take you to the WordPress overview. Click Install and it will take you to the installer interface.

The screenshot shows the WordPress installation interface within a cPanel environment. The top navigation bar includes 'Sofaculous', 'PHP', 'JavaScripts', 'PERL', and 'Classes'. A search bar is present on the left. The main content area displays the WordPress logo, version '4.4.2', and release date '02-02-2016'. A navigation menu includes 'Install', 'Overview', 'Features', 'Screenshots', 'Demo', 'Ratings', 'Reviews', and 'Import'. The 'Install' button is highlighted with a red circle. Below the navigation menu, there is a preview of a WordPress blog with a 'Hello world!' post. To the right, there is a description of WordPress and its requirements, including 'Space Required' information.

Step (3) – You will be asked for some configuration, which are explained below.

The screenshot shows the 'Software Setup' configuration page for WordPress. The page includes the WordPress logo, version '4.4.2', and release date '02-02-2016'. A navigation menu includes 'Install', 'Overview', 'Features', 'Screenshots', 'Demo', 'Ratings', 'Reviews', and 'Import'. The 'Install' button is highlighted. Below the navigation menu, there is a 'Software Setup' section with three configuration options: 'Choose Protocol' (set to 'http://'), 'Choose Domain' (set to 'tutorialspoint.com'), and 'In Directory' (set to 'wp').

- **Choose Protocol** – Choose protocol of your WordPress website. You can use http or https with or without www. If you choose https, then a SSL certificate must be installed in your website. You can change this setting later in WordPress setting, if required.
- **Choose Domain** – You can install your WordPress in the root domain or any subdomain you created, choose from the dropdown menu.
- **In Directory** – Choose the folder in which you wish to install the WordPress. If you want to install in your root website, make this field empty.

Site Settings

Site Name

Site Description

Enable Multisite (WPMU)

- **Site Name** – Give a name to your website in this field.
- **Site Description** – Provide a short description of your website.
- **Enable Multisite** – If Checked, then it will install a WordPress network installation.

Admin Account

Admin Username

Admin Password 
Strong (60/100)

Admin Email

- **Admin Username/Password** – Enter your administrator username and password, you will need these to login to your admin panel later.
- **Admin Email** – Enter the email address on which you want to receive the important notification of your WordPress.

Choose Language

Select Language

- **Select Language** – Choose a language for your WordPress Installation.

Select Plugins

Limit Login Attempts (Loginizer)

- **Plugins** – You can select to install these 3rd Party Plugins, this is optional.

Advanced Options

Database Name
Type the name of the database to be created for the installation

Table Prefix

Disable Update Notifications

Auto Upgrade

Auto Upgrade WordPress Plugins

Auto Upgrade WordPress Themes

Automated backups

Backup Rotation

- **Database Name** – You can specify a custom database name for your WordPress database, or you can leave this setting as it is.
- **Table Prefix** – If you are going to use the same database for more than one installation, you can specify table prefix here. All the tables that will be created will have this prefix before them.
- **Disable Update Notifications** – You can choose not to receive update notification on your admin email by selecting this checkbox.
- **Upgrade Options** – You can choose to auto upgrade your WordPress CMS, Installed theme or Installed plugins. Select appropriate options.
- **Automated backups** – You can choose to create a backup of your WordPress automatically using Softaculous Apps Installer, if selected you can choose a backup rotation for your system.

- **Select Theme** – If you select any theme here, then Softaculous Apps Installer will make an auto install of that theme. If you do not choose any theme then a clean WordPress Installation will be done.

Step (4) – Click Install to install the WordPress CMS on your website. If successful, you will be given the links to your installation and admin panel.

63. cPanel – FileZilla FTP Client


FileZilla is an open source FTP client, it is available on multiple platforms like Linux and Windows. This client also supports FTP over secured connections that is SFTP and FTPS. You can use this software to upload and manage your files in your webserver. When you wish to upload your website and number of files are more or size of files are very large. Then you can use FTP upload, because uploading a file of very large size through cPanel File Manager can cause an error in uploading.

Most of the cPanel accounts comes with a system FTP account, through which you can access and manage all the files in your home directory. Passwords of system account for cPanel and FTP are same in most cases.

To use FileZilla FTP client, to manage and upload the website, please follow these steps:

Step (1) – Download and install FileZilla FTP client from FileZilla website. The installation process of this software is the same as other software's.


<https://filezilla-project.org/download.php>



Step (2) – After installing open your FileZilla FTP client. In the quick connect bar, you will find text box to provide hostname. Enter your ftp hostname, which can be IP address of your server or **ftp.<your_domain.com>**.

Step (3) – Enter the username and password for your ftp account.

Step (4) – Enter Port on which you want to connect to your FTP server. In most of the cases, it is 21, but if you leave this field empty then FileZilla will automatically find the appropriate port to connect.



Step (5) – Click Quickconnect to connect to the FTP server.

Step (6) – After a successful connection, you can move or copy files from the left hand side pane (which are your local computer directories) to the Right hand side pane (which are your remote server directories and files). You can drag and drop files from the left to right pane or vice versa.


Step (7) – You can view the status of your moving or copying in the pane, which is on the lower side of the interface.

64. cPanel – CloudFlare


CloudFlare is a CDN (Content Delivery Network) with both free and paid plans. Most cPanel hosting comes with cPanel CloudFlare plugin, which helps you to quickly sign up for CloudFlare and use their CDN. Using CloudFlare has many advantages like it distributes the content over the Internet making our website load faster. It protects the website from SQL injection and DDOS and encrypts the website using SSL.

To use CloudFlare CDN, please follow these steps:

Step (1) – Open CloudFlare interface by clicking CloudFlare found in the cPanel Home under CloudFlare – Supercharge your website section.



Step (2) – In CloudFlare Interface under Sign Up / Log In, Enter your email address and click Signup Now. If you have an existing account with CloudFlare, it will ask you to login, otherwise it will sign you up.



Step (3) – Once you are logged in, you can see the status of your domain in overview section of CloudFlare interface. You will need to change your current Nameservers to those provided by CloudFlare to use it with your website. If you do not like services of CloudFlare, then you can change your domain's Nameservers back to default.

Change Your Nameservers

Your website will not experience any downtime when you change your nameservers.

We could not detect the registrar for tutorialspoint.com

i The transfer process can take up to 24 hours. There will be no downtime when you switch your name servers. Traffic will gracefully roll from your old name servers to the new name servers without interruption. Your site will remain available throughout the switch.

Current Nameservers	Change Nameservers to:
ns1.edgecastdns.net	cloe.ns.cloudflare.com
ns2.edgecastdns.net	ian.ns.cloudflare.com
ns3.edgecastdns.net	Remove this nameserver
ns4.edgecastdns.net	Remove this nameserver

[Help >](#)

Step (4) – Once you have updated your Nameservers, you can use CloudFlare CDN. You can also view and configure your website for CloudFlare on their website.